

TRIO 3X RQ 220 LED PLUS P 2900LM DALI 840 IP65/IP20 I CL. MAT 24W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	24
Luminous flux [lm]*:	2900
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	121
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	4000
Beam angle [°]:	110
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

RQ 220 LED P PLUS is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

The lamp is especially recommended for office spaces, spacious corridors and public spaces.

TRIO 3X RQ 220 LED PLUS P 2900LM DALI 840 IP65/IP20 I CL. MAT 24W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	947742	Mounting dimensions [mm]:	200
EAN:	5905963947742	Impact resistance:	IK07
Light source:	LED module	Ingress protection:	IP65/IP20
Rated power of the luminaire [W]:	24	Mounting version:	recessed
Luminous flux [lm]:	2900	Working temperature [°C]:	from 0 to +35
Supply voltage [V]:	220-240	Number on the palette [pcs]:	28
Frequency [Hz]:	50-60	Net weight [kg]:	1.450
Luminous efficacy [lm/W]:	121	Product line:	Trio
Energy efficiency class:	D	DIMM DALI:	yes
Electrical protection class:	I	Category type:	downlights
Colour temperature [K]:	4000	LED lifespan L70B50 [h]:	132000
Color rendering index (Ra) >:	80	LED lifespan L80B10 [h]:	84000
Beam angle [°]:	110	LED lifespan L90B10 [h]:	42000
Light distribution type:	lambertian	Version:	Trio (3 pieces)
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	OPAL	CE certificate:	302/2023
Material of the body:	ABS	HACCP:	852/2004
Colour of the body:	white	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	221/221/51	Plik LDT:	Download

Card creation date: 23 January 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 302/2023