

# TRIO 3X RQ 220 LED PLUS P 2700LM DALI 830 IP65/IP20 I CL. MAT 24W

DETAILED CARD



## TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	24
Luminous flux [lm]*:	2700
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	113
Energy efficiency class:	E
Electrical protection class:	I
Colour temperature [K]:	3000
Beam angle [°]:	110
Diffuser material:	PC
Diffuser type:	OPAL

## CHARACTERISTICS

RQ 220 LED P PLUS is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

## APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

The lamp is especially recommended for office spaces, spacious corridors and public spaces.

# TRIO 3X RQ 220 LED PLUS P 2700LM DALI 830 IP65/IP20 I CL. MAT 24W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	947759	Mounting dimensions [mm]:	200
EAN:	5905963947759	Impact resistance:	IK07
Light source:	LED module	Ingress protection:	IP65/IP20
Rated power of the luminaire [W]:	24	Mounting version:	recessed
Luminous flux [lm]:	2700	Working temperature [°C]:	from 0 to +35
Supply voltage [V]:	220-240	Number on the palette [pcs]:	28
Frequency [Hz]:	50-60	Net weight [kg]:	1.450
Luminous efficacy [lm/W]:	113	Product line:	Trio
Energy efficiency class:	E	DIMM DALI:	yes
Electrical protection class:	I	Category type:	downlights
Colour temperature [K]:	3000	LED lifespan L70B50 [h]:	132000
Colour rendering index:	80	LED lifespan L80B20 [h]:	84000
Beam angle [°]:	110	LED lifespan L90B10 [h]:	42000
Light distribution type:	lamertian	Version:	Trio (3 pieces)
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	OPAL	CE certificate:	<a href="#">302/2023</a>
Material of the body:	ABS	HACCP:	<a href="#">852/2004</a>
Colour of the body:	white	Manual:	<a href="#">Download PDF</a>
Dimensions (H/W/T/S) [mm]:	221/221/51	Plik LDT:	<a href="#">Download</a>