

# TRIO 3X RQ 220 LED PLUS P 2700LM DALI 830 IP65/IP20 I CL. MAT 24W

DETAILED CARD



## TECHNICAL PARAMETERS

|                                    |                |
|------------------------------------|----------------|
| Rated power of the luminaire [W]*: | 17             |
| Luminous flux [lm]*:               | max 3300       |
| Frequency [Hz]:                    | 50-60          |
| Energy efficiency class:           | C; D; E        |
| Electrical protection class:       | I; II          |
| Colour temperature [K]:            | 3000; 4000     |
| Beam angle [°]:                    | 110; 115       |
| Diffuser material:                 | PC             |
| Diffuser type:                     | MAT; OPAL; PRM |

## CHARACTERISTICS

RQ 220 LED P PLUS is a new line of round downlights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

## APPLICATION

Designed from scratch, the design introduces new solutions to ensure excellent light performance. The body is made of plastic, so it is characterized by low weight. The lampshade provides the lamp with excellent light characteristics. Integrated LED module Provides low electricity consumption and all the advantages of modern lamps with LED source for investment lighting.

The lamp is especially recommended for office spaces, spacious corridors and public spaces.

# TRIO 3X RQ 220 LED PLUS P 2700LM DALI 830 IP65/IP20 I CL. MAT 24W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |                |                              |   |
|-----------------------------------|----------------|------------------------------|---|
| Index:                            | x              | Mounting dimensions [mm]:    | 200   |
| EAN:                              | x              | Impact resistance:           | IK07  |
| Light source:                     | moduł LED      | Ingress protection:          | IP65/IP20                                   |
| Rated power of the luminaire [W]: | 17             | Mounting version:            | podtynkowy                                  |
| Luminous flux [lm]:               | max 3300       | Working temperature [°C]:    | od 0 do +25; od 0 do +35                    |
| Supply voltage [V]:               | 220-240        | Number on the palette [pcs]: | 28; 130; 285                                |
| Frequency [Hz]:                   | 50-60          | Product line:                | Trio  |
| Energy efficiency class:          | C; D; E        | DIMM DALI:                   | yes   |
| Electrical protection class:      | I; II          | Category type:               | downlights                                  |
| Colour temperature [K]:           | 3000; 4000     | LED lifespan L70B50 [h]:     | 132000                                      |
| Colour rendering index:           | >80            | LED lifespan L80B20 [h]:     | 84000                                       |
| Beam angle [°]:                   | 110; 115       | LED lifespan L90B10 [h]:     | 42000                                       |
| Light distribution type:          | lambertowski   | Version:                     | Trio (3 sztuki)                             |
| Diffuser material:                | PC             | Warranty [years]:            | 2; 5  |
| Diffuser type:                    | MAT; OPAL; PRM | CE certificate:              | <a href="#">11/2023; 301/2023; 302/2023</a> |
| Material of the body:             | ABS            | HACCP:                       |   |
| Colour of the body:               | biały          | Manual:                      | <a href="#">Download PDF</a>                |
| Dimensions (H/W/T/S) [mm]:        | 221/221/51     |                              |   |