## **ALTEZZO L 100 900MM 700LM 830 IP65 RAL7016 6W**

**DETAILED CARD** 



#### **TECHNICAL PARAMETERS**

Rated power of the luminaire [W]*:	6
Luminous flux [lm]*:	700
Luminous efficacy [lm/W]:	117
Energy efficiency class:	D
Electrical protection class:	1
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Beam angle [°]:	110
Diffuser material:	PC

#### **CHARACTERISTICS**

Altezzo L 100 is a family of outdoor lamps with a modern design. They are offered in four sizes - with heights ranging from 600 mm to 1500 mm. Their impact-resistant (IK08) and compact profile (100 mm x 40 mm) is made of aluminum in graphite color (RAL 7016). The light module consists of leds with a life span of up to 196,000 h, with lenses made of PMMA and a durable polycarbonate diffuser.

#### **APPLICATION**

The wide range of luminous fluxes in the Altezzo L 100 lamp series allows to design energy-efficient lighting in the amount required by the norm, both in walking alleys and building surroundings. Versions with lower wattages will work well in parks and gardens for illuminating small architecture.

The lamps are designed for operation in low and high temperatures from -30°C to +50°C and in harsh weather conditions. They are characterized by a very high IP65 tightness.

### **DETAILS**

The selection of the foundation for the lighting column, in accordance with the Building Act, rests with the designer, with the relevant qualifications. The designer is also obliged to check the standard solution from the lighting manufacturer's offer, as he knows, among other things, the soil and water conditions in the designed area. If the dedicated foundation does not provide the safe conditions specified in the design, a suitable one should be selected from outside the lighting manufacturer's offer, with an anchor spacing of 180x180 - 220x220mm. As standard, in the case of **Altezzo L100**, universal 13kg foundations are used for garden lamps or FBO 35/7.5 M6 foundations for taller posts and/or more difficult ground and water conditions.



# **ALTEZZO L 100 900MM 700LM 830 IP65 RAL7016 6W**

**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

Index:	984099
EAN:	5905963984099
Light source:	LED module
Rated power of the luminaire [W]:	6
Luminous flux [Im]:	700
Luminous efficacy [lm/W]:	117
Energy efficiency class:	D
Electrical protection class:	1
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
LED lifespan L70B50 [h]:	196000
LED lifespan L80B20 [h]:	123000
LED lifespan L90B10 [h]:	60000
Beam angle [°]:	110
Light distribution type:	general
Diffuser material:	PC
Material of the body:	aluminium

Colour of the body:	RAL7016
Dimensions (H/W/T/S) [mm]:	900/100/40/200
Mounting dimensions [mm]:	75x75 - 90x90
Impact resistance:	IK08
Ingress protection:	IP65
Mounting version:	on a foundation
Working temperature [°C]:	od -30 do +50
Dimensions of single box [mm]:	207/143/905
Number on the palette [pcs]:	48
Net weight [kg]:	3
Category type:	Park and city lighting
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	5
CE certificate:	93/2023
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 27 October 2025



