

ALTEZZO L 100 1500MM 1400LM 840 IP65 RAL7016 12W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	12
Luminous flux [lm]*:	1400
Luminous efficacy [lm/W]:	117
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	4000
Colour rendering index:	80
Beam angle [°]:	110
Diffuser material:	PC

CHARACTERISTICS

Altezzo L 100 is a family of outdoor lamps with a modern design. They are offered in four sizes - with heights ranging from 600 mm to 1500 mm. Their impact-resistant (IK08) and compact profile (100 mm x 40 mm) is made of aluminum in graphite color (RAL 7016). The light module consists of leds with a life span of up to 196,000 h, with lenses made of PMMA and a durable polycarbonate diffuser.

APPLICATION

The wide range of luminous fluxes in the Altezzo L 100 lamp series allows to design energy-efficient lighting in the amount required by the norm, both in walking alleys and building surroundings. Versions with lower wattages will work well in parks and gardens for illuminating small architecture.

The lamps are designed for operation in low and high temperatures from -30°C to +50 °C and in harsh weather conditions. They are characterized by a very high IP65 tightness.

DETAILS

The selection of the foundation for the lighting column, in accordance with the Building Act, rests with the designer, with the relevant qualifications. The designer is also obliged to check the standard solution from the lighting manufacturer's offer, as he knows, among other things, the soil and water conditions in the designed area. If the dedicated foundation does not provide the safe conditions specified in the design, a suitable one should be selected from outside the lighting manufacturer's offer, with an anchor spacing of 180x180 - 220x220mm. As standard, in the case of **Altezzo L100**, universal 13kg foundations are used for garden lamps or FBO 35/7.5 M6 foundations for taller posts and/or more difficult ground and water conditions.

ALTEZZO L 100 1500MM 1400LM 840 IP65 RAL7016 12W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	984075	Colour of the body:	RAL7016
EAN:	5905963984075	Dimensions (H/W/T/S) [mm]:	1500/100/40/200
Light source:	LED module	Mounting dimensions [mm]:	75x75 - 90x90
Rated power of the luminaire [W]:	12	Impact resistance:	IK08
Luminous flux [lm]:	1400	Ingress protection:	IP65
Luminous efficacy [lm/W]:	117	Mounting version:	on a foundation
Energy efficiency class:	D	Working temperature [°C]:	od -30 do +50
Electrical protection class:	I	Dimensions of single box [mm]:	207/143/1505
Colour temperature [K]:	4000	Number on the palette [pcs]:	24
Colour rendering index:	80	Net weight [kg]:	4
LED lifespan L70B50 [h]:	196000	Category type:	Park and city lighting
LED lifespan L80B20 [h]:	123000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L90B10 [h]:	60000	Warranty [years]:	5
Beam angle [°]:	110	CE certificate:	93/2023
Light distribution type:	general	Manual:	Download PDF
Diffuser material:	PC	Plik LDT:	Download
Material of the body:	aluminium		