

ALTEZZO L 150 5000MM 3850LM 727 DALI IP65 RAL7016 32W

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK09
Luminous flux [lm]*:	3850
Colour temperature [K]:	2700
Material of the body:	aluminium
Colour of the body:	RAL7016
Diffuser material:	PC
Beam angle [°]:	110
Mounting version:	on a foundation
Dimensions (H/W/T/S) [mm]:	5000/150/150/800

CHARACTERISTICS

Altezzo L 150 is a family of outdoor lamps with a modern design. We offer them in five dimensions - with heights ranging from 2500 mm to 5000 mm. Their construction provides for the possibility of customising the lamp in accordance with the designer or architect's guidelines. The lamp component containing the light module can be oriented parallel to the plane to be illuminated. In addition, the profile itself can bifurcate. As a result, up to four light module elements can be mounted on a single post - one on each plane of the post - at the same or different heights.

The compact (150 mm x 150 mm), square cross-section profile of the Altezzo lamps is impact-resistant (IK09). It is made of aluminium in graphite (RAL 7016). The light module is made up of leds with a lifetime of up to 196,000 h, with lenses made of PMMA and a durable polycarbonate diffuser.

The Altezzo lamp is available with dozens of types of light distribution. The designer has the option of choosing one that ensures not only that the stringent standards are met, but also that the lighting is adequate, energy-efficient and that the users are safe.

APPLICATION

The wide range of wattages, luminous fluxes and light distributions of the Altezzo L 150 lamp series make it possible to design energy-efficient lighting for roads, pavements, car parks, residential streets or walkways. The lower wattage versions are also suitable for parks and gardens, to illuminate street furniture.

The lamps are designed to operate in very low and high temperatures from -30°C to +50°C and in harsh weather conditions. They are characterised by very high IP65 tightness.

ALTEZZO L 150 5000MM 3850LM 727 DALI IP65 RAL7016 32W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	986185	Dimensions (H/W/T/S) [mm]:	5000/150/150/800
EAN:	5905963986185	Mounting dimensions [mm]:	180x180 - 220x220
Light source:	LED module	Impact resistance:	IK09
Rated power of the luminaire [W]:	32	Ingress protection:	IP65
Luminous flux [lm]:	3850	Mounting version:	on a foundation
Luminous efficacy [lm/W]:	121	Working temperature [°C]:	od - 30 do + 50
Energy efficiency class:	D	DIMM DALI:	yes
Electrical protection class:	I	Net weight [kg]:	41
Colour temperature [K]:	2700	CE certificate:	92/2023
Colour rendering index:	>70	Warranty [years]:	5
Beam angle [°]:	110	Category type:	Park and city lighting
Diffuser material:	PC	Light distribution type:	general
Material of the body:	aluminium	Manual:	Download PDF
Colour of the body:	RAL7016		

Card creation date: 09 February 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 92/2023