

# ALTEZZO L 100 K 650LM 840 IP65 RAL7016 5W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Rated power of the luminaire [W]*:</b>	5
<b>Luminous flux [lm]*:</b>	650
<b>Ingress protection:</b>	IP65
<b>Impact resistance:</b>	IK08
<b>Colour temperature [K]:</b>	4000
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	RAL7016
<b>Diffuser material:</b>	PC
<b>Beam angle [°]:</b>	110
<b>Mounting version:</b>	surface

## CHARACTERISTICS

The Altezzo L 100 K wall lamp completes the entire line of outdoor lighting from the Altezzo series. It is characterized by a classic, simple shape and good light and mechanical parameters. It is available with two light color temperatures of 3000 K and 4000 K.

## APPLICATION

The sconce's high IP65 waterproofing and IK08 impact resistance allow it to be used outdoors. It will prove useful as lighting for facades and building surroundings. Together with other products of the Altezzo line, it will provide good, eye-friendly and safety-friendly lighting and design consistency in housing estates, parks and gardens.

# ALTEZZO L 100 K 650LM 840 IP65 RAL7016 5W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	984341	<b>Mounting dimensions [mm]:</b>	70x22
<b>EAN:</b>	5905963984341	<b>Impact resistance:</b>	IK08
<b>Light source:</b>	LED module	<b>Ingress protection:</b>	IP65
<b>Rated power of the luminaire [W]:</b>	5	<b>Mounting version:</b>	surface
<b>Luminous flux [lm]:</b>	650	<b>Working temperature [°C]:</b>	od - 30 do + 50
<b>Luminous efficacy [lm/W]:</b>	130	<b>Net weight [kg]:</b>	1.300
<b>Colour temperature [K]:</b>	4000	<b>CE certificate:</b>	<a href="#">183/2023</a>
<b>Energy efficiency class:</b>	D	<b>Warranty [years]:</b>	5
<b>Beam angle [°]:</b>	110	<b>Category type:</b>	accent lighting
<b>Electrical protection class:</b>	I	<b>LED lifespan L70B50 [h]:</b>	196000
<b>Dimensions (H/W/T/S) [mm]:</b>	40/100/250	<b>LED lifespan L80B20 [h]:</b>	123000
<b>Colour rendering index:</b>	>80	<b>LED lifespan L90B10 [h]:</b>	60000
<b>Diffuser material:</b>	PC	<b>Light distribution type:</b>	general
<b>Material of the body:</b>	aluminium	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Colour of the body:</b>	RAL7016		

Card creation date: 14 February 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 183/2023