

ALTEZZO L 100 K 600LM 830 IP65 RAL7016 5W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	5
Luminous flux [lm]*:	600
Luminous efficacy [lm/W]:	120
Energy efficiency class:	D
Electrical protection class:	I
Material of the body:	aluminium
Colour of the body:	RAL7016
Dimensions (H/W/T/S) [mm]:	40/100/250
Impact resistance:	IK08
Ingress protection:	IP65

CHARACTERISTICS

The Altezzo L 100 K wall lamp completes the entire line of outdoor lighting from the Altezzo series. It is characterized by a classic, simple shape and good light and mechanical parameters. It is available with two light color temperatures of 3000 K and 4000 K.

APPLICATION

The sconce's high IP65 waterproofing and IK08 impact resistance allow it to be used outdoors. It will prove useful as lighting for facades and building surroundings. Together with other products of the Altezzo line, it will provide good, eye-friendly and safety-friendly lighting and design consistency in housing estates, parks and gardens.

ALTEZZO L 100 K 600LM 830 IP65 RAL7016 5W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	984358	Colour of the body:	RAL7016
EAN:	5905963984358	Dimensions (H/W/T/S) [mm]:	40/100/250
Light source:	LED module	Mounting dimensions [mm]:	70x22
Rated power of the luminaire [W]:	5	Impact resistance:	IK08
Luminous flux [lm]:	600	Ingress protection:	IP65
Luminous efficacy [lm/W]:	120	Mounting version:	surface
Energy efficiency class:	D	Working temperature [°C]:	od -30 do +50
Electrical protection class:	I	Dimensions of single box [mm]:	45/105/255
Colour temperature [K]:	3000	Number on the palette [pcs]:	510
Color rendering index (Ra) >:	80	Net weight [kg]:	1.300
LED lifespan L70B50 [h]:	196000	Category type:	accent lighting
LED lifespan L80B20 [h]:	123000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L90B10 [h]:	60000	Warranty [years]:	5
Beam angle [°]:	110	CE certificate:	183/2023
Light distribution type:	general	Manual:	Download PDF
Diffuser material:	PC	Environmental Product Declaration (EPD):	852/2025
Material of the body:	aluminium	Plik LDT:	Download

Card creation date: 16 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).  Certificate CE - Nr: 183/2023