

ALTEZZO L 100 K 600LM 830 IP65 RAL7016 5W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	5
Luminous flux [lm]*:	600
Ingress protection:	IP65
Impact resistance:	IK08
Colour temperature [K]:	3000
Material of the body:	aluminium
Colour of the body:	RAL7016
Diffuser material:	PC
Beam angle [°]:	110
Mounting version:	surface

CHARACTERISTICS

The Altezzo L 100 K wall lamp completes the entire line of outdoor lighting from the Altezzo series. It is characterized by a classic, simple shape and good light and mechanical parameters. It is available with two light color temperatures of 3000 K and 4000 K.

APPLICATION

The sconce's high IP65 waterproofing and IK08 impact resistance allow it to be used outdoors. It will prove useful as lighting for facades and building surroundings. Together with other products of the Altezzo line, it will provide good, eye-friendly and safety-friendly lighting and design consistency in housing estates, parks and gardens.

ALTEZZO L 100 K 600LM 830 IP65 RAL7016 5W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	984358	Mounting dimensions [mm]:	70x22
EAN:	5905963984358	Impact resistance:	IK08
Light source:	LED module	Ingress protection:	IP65
Rated power of the luminaire [W]:	5	Mounting version:	surface
Luminous flux [lm]:	600	Working temperature [°C]:	od - 30 do + 50
Luminous efficacy [lm/W]:	120	Net weight [kg]:	1.300
Energy efficiency class:	D	CE certificate:	183/2023
Electrical protection class:	I	Warranty [years]:	5
Colour temperature [K]:	3000	Category type:	accent lighting
Colour rendering index:	>80	LED lifespan L70B50 [h]:	196000
Beam angle [°]:	110	LED lifespan L80B20 [h]:	123000
Diffuser material:	PC	LED lifespan L90B10 [h]:	60000
Material of the body:	aluminium	Light distribution type:	general
Colour of the body:	RAL7016	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	40/100/250	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)