

# ALTEZZO L 150 K 5200LM 840 IP65 RAL7016 40W

DETAILED CARD



## TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK08
Luminous flux [lm]*:	5200
Colour temperature [K]:	4000
Material of the body:	aluminium
Colour of the body:	RAL7016
Diffuser material:	PC
Beam angle [°]:	110
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	150/150/500

## CHARACTERISTICS

The Altezzo L 150 K wall lamp completes the entire line of outdoor lighting from the Altezzo series. It is characterized by a classic, simple shape and good light and mechanical parameters. It is available with three light color temperatures 2700 K 3000 K and 4000 K.

## APPLICATION

The sconce's high IP65 waterproofing and IK08 impact resistance allow it to be used outdoors. It will prove useful as lighting for facades and building surroundings. Together with other products of the Altezzo line, it will provide good, eye-friendly and safety-friendly lighting and design consistency in housing estates, parks and gardens.

# ALTEZZO L 150 K 5200LM 840 IP65 RAL7016 40W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	984365	Dimensions (H/W/T/S) [mm]:	150/150/500
EAN:	5905963984365	Mounting dimensions [mm]:	75x75 - 90x90
Light source:	LED module	Impact resistance:	IK08
Rated power of the luminaire [W]:	40	Ingress protection:	IP65
Luminous flux [lm]:	5200	Mounting version:	surface
Luminous efficacy [lm/W]:	130	Working temperature [°C]:	od -30 do +50
Energy efficiency class:	D	Net weight [kg]:	3.200
Electrical protection class:	I	CE certificate:	<a href="#">181/2023</a>
Colour temperature [K]:	4000	Warranty [years]:	5
Colour rendering index:	70	Category type:	accent lighting
Beam angle [°]:	110	Light distribution type:	general
Diffuser material:	PC	Manual:	<a href="#">Download PDF</a>
Material of the body:	aluminium	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour of the body:	RAL7016		