ALTEZZO L 150 K 4900LM 830 IP65 RAL7016 40W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	40
Luminous flux [lm]*:	4900
Luminous efficacy [lm/W]:	123
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	3000
Diffuser material:	PC
Dimensions (H/W/T/S) [mm]:	150/150/500

CHARACTERISTICS

The Altezzo L 150 K wall lamp completes the entire line of outdoor lighting from the Altezzo series. It is characterized by a classic, simple shape and good light and mechanical parameters. It is available with three light color temperatures2700 K 3000 K and 4000 K.

APPLICATION

The sconce's high IP65 waterproofing and IK08 impact resistance allow it to be used outdoors. It will prove useful as lighting for facades and building surroundings. Together with other products of the Altezzo line, it will provide good, eye-friendly and safety-friendly lighting and design consistency in housing estates, parks and gardens.

ALTEZZO L 150 K 4900LM 830 IP65 RAL7016 40W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	984372
EAN:	5905963984372
Light source:	LED module
Rated power of the luminaire [W]:	40
Luminous flux [lm]:	4900
Luminous efficacy [lm/W]:	123
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	3000
Color rendering index (Ra) >:	70
Beam angle [°]:	110
Light distribution type:	general
Diffuser material:	PC
Material of the body:	aluminium
Colour of the body:	RAL7016
Dimensions (H/W/T/S) [mm]:	150/150/500

Mounting dimensions [mm]:	75x75 - 90x90
Impact resistance:	IK08
Ingress protection:	IP65
Mounting version:	surface
Working temperature [°C]:	od -30 do +50
Dimensions of single box [mm]:	155/155/505
Number on the palette [pcs]:	82
Net weight [kg]:	3.200
Category type:	accent lighting
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	5
CE certificate:	181/2023
Manual:	Download PDF
Environmental Product Declaration (EPD):	852/2025
Plik LDT:	Download

Card creation date: 16 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 181/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl