

ALTEZZO L 150 K 4900LM 830 IP65 RAL7016 40W

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK08
Luminous flux [lm]*:	4900
Colour temperature [K]:	3000
Material of the body:	aluminium
Colour of the body:	RAL7016
Diffuser material:	PC
Beam angle [°]:	110
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	150/150/500

CHARACTERISTICS

APPLICATION

ALTEZZO L 150 K 4900LM 830 IP65 RAL7016 40W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	984372	Colour of the body:	RAL7016
EAN:	5905963984372	Dimensions (H/W/T/S) [mm]:	150/150/500
Light source:	LED module	Mounting dimensions [mm]:	75x75 - 90x90
Rated power of the luminaire [W]:	40	Impact resistance:	IK08
Luminous flux [lm]:	4900	Ingress protection:	IP65
Luminous efficacy [lm/W]:	123	Mounting version:	surface
Energy efficiency class:	D	Working temperature [°C]:	od - 30 do + 50
Electrical protection class:	I	Net weight [kg]:	3.200
Colour temperature [K]:	3000	CE certificate:	181/2023
Colour rendering index:	>70	Warranty [years]:	5
Beam angle [°]:	110	Category type:	accent lighting
Diffuser material:	PC	Light distribution type:	general
Material of the body:	aluminium	Manual:	Download PDF

Card creation date: 10 February 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 181/2023