

ALTEZZO L 150 K 4600LM 827 IP65 RAL7016 40W

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK08
Luminous flux [lm]*:	4600
Colour temperature [K]:	2700
Material of the body:	aluminium
Colour of the body:	RAL7016
Diffuser material:	PC
Beam angle [°]:	110
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	150/150/500

CHARACTERISTICS

The Altezzo L 150 K wall lamp completes the entire line of outdoor lighting from the Altezzo series. It is characterized by a classic, simple shape and good light and mechanical parameters. It is available with three light color temperatures 2700 K 3000 K and 4000 K.

APPLICATION

The sconce's high IP65 waterproofing and IK08 impact resistance allow it to be used outdoors. It will prove useful as lighting for facades and building surroundings. Together with other products of the Altezzo line, it will provide good, eye-friendly and safety-friendly lighting and design consistency in housing estates, parks and gardens.

ALTEZZO L 150 K 4600LM 827 IP65 RAL7016 40W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	984389	Dimensions (H/W/T/S) [mm]:	150/150/500
EAN:	5905963984389	Mounting dimensions [mm]:	75x75
Light source:	LED module	Impact resistance:	IK08
Rated power of the luminaire [W]:	40	Ingress protection:	IP65
Luminous flux [lm]:	4600	Mounting version:	surface
Luminous efficacy [lm/W]:	115	Working temperature [°C]:	od -30 do +50
Energy efficiency class:	D	Net weight [kg]:	3.200
Electrical protection class:	I	CE certificate:	181/2023
Colour temperature [K]:	2700	Warranty [years]:	5
Colour rendering index:	70	Category type:	accent lighting
Beam angle [°]:	110	Light distribution type:	general
Diffuser material:	PC	Manual:	Download PDF
Material of the body:	aluminium	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour of the body:	RAL7016		