

PIATTO SUSPENDED FI 340MM 520LM I KL. BLACK-GOLD IP20 830 (9W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|-------------------------|
| Index: | 654060 |
| Ingress protection: | IP20 |
| Nominal power [W]: | 9 |
| Luminous flux [lm]*: | 520 |
| Colour temperature [K]: | 3000 |
| Colour rendering index: | >80 |
| Energy efficiency class: | G |
| Material of the body: | powder coated aluminium |
| Colour of the body: | black-gold |
| Diffuser material: | PC |

CHARACTERISTICS

The PIATTO line of luminaires is distinguished by its elegant design that allows it to be used in a variety of arrangements. The minimalist aluminum shades, available as standard in three fashionable color schemes, will emphasize the ambience of every interior, creating a strong decorative accent. The integrated energy-saving LED GO! panel ensures high light quality and long-term trouble-free use.

APPLICATION

A lightweight, suspended or surface-mounted PIATTO luminaire will brighten up rooms that are to stand out with their aesthetics. It can be used in public areas, such as restaurants and hotels, as well as in private apartments.

PIATTO SUSPENDED FI 340MM 520LM I KL. BLACK-GOLD IP20 830 (9W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------|----------------------------|------------------------------|
| Nominal power [W]: | 9 | Material of the body: | powder coated aluminium |
| Rated power of the luminaire [W]: | 9.30 | Dimensions (H/W/T/S) [mm]: | ø340/280/1500 |
| Colour temperature [K]: | 3000 | Ingress protection: | IP20 |
| Luminous flux [lm]: | 520 | Mounting version: | suspended |
| Colour of the body: | black-gold | Working temperature [°C]: | from -25 to +25 |
| Energy efficiency class: | G | Net weight [kg]: | 2.300 |
| Light source: | LED module | CE certificate: | 221/2023 |
| Supply voltage [V]: | 220-240 | Index: | 654060 |
| Frequency [Hz]: | 50 - 60 | EAN: | 5905963654060 |
| Luminous efficacy [lm/W]: | 55 | Category type: | architectural, downlights |
| Electrical protection class: | I | Cable length [m]: | 1.50 |
| Colour rendering index: | >80 | ETIM class: | EC001743 |
| Power factor: | 0.53 | Manual: | Download PDF |
| Diffuser material: | PC | Plik LDT: | |
| Diffuser type: | OPAL | | |

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 221/2023