PIATTO SUSPENDED FI 340MM 520LM I KL. BLACK-GOLD IP20 830 (9W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	654060
Ingress protection:	IP20
Nominal power [W]:	9
Luminous flux [lm]*:	520
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Energy efficiency class:	G
Material of the body:	powder coated aluminium
Colour of the body:	black-gold
Diffuser material:	PC

CHARACTERISTICS

The PIATTO line of luminaires is distinguished by its elegant design that allows it to be used in a variety of arrangements. The minimalist aluminum shades, available as standard in three fashionable color schemes, will emphasize the ambience of every interior, creating a strong decorative accent. The integrated energy-saving LED GO! panel ensures high light quality and long-term trouble-free use.

APPLICATION

A lightweight, suspended or surface-mounted PIATTO luminaire will brighten up rooms that are to stand out with their aesthetics. It can be used in public areas, such as restaurants and hotels, as well as in private apartments.

PIATTO SUSPENDED FI 340MM 520LM I KL. BLACK-GOLD IP20 830 (9W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	9
Rated power of the luminaire [W]:	9.30
Colour temperature [K]:	3000
Luminous flux [lm]:	520
Colour of the body:	black-gold
Energy efficiency class:	G
Light source:	LED module
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	55
Electrical protection class:	I
Color rendering index (Ra) >:	80
Power factor:	0.53
Diffuser material:	PC
Diffuser type:	OPAL

Material of the body:	powder coated aluminium
Dimensions (H/W/T/S) [mm]:	ø340/280/1500
Ingress protection:	IP20
Mounting version:	suspended
Working temperature [°C]:	from -25 to +25
Net weight [kg]:	2.300
CE certificate:	221/2023
Index:	654060
EAN:	5905963654060
Category type:	decorative fixtures
Cable length [m]:	1.50
ETIM class:	EC001743
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 221/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl