


SATURN SMD LED 9W KLOSZ MAT BIAŁY AW 2H 4000K AUTOTEST

DETAILED CARD



TECHNICAL PARAMETERS

Index:	069055/PA
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	9
Luminous flux [lm]*:	870
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Electrical protection class:	I
Energy efficiency class:	F

CHARACTERISTICS

Surface mounted, round LED light fixture with a high luminous flux, high ingress protection class IP54 and an integrated energy-saving light source LED GO!. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). Available ring colors; optional equipment: radio motion sensor (RCR) or PIR sensor.

APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for outdoor (façade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms.


SATURN SMD LED 9W KLOSZ MAT BIAŁY AW 2H 4000K AUTOTEST

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions (H/W/T/S) [mm]:	ø335/110
Nominal power [W]:	9	Impact resistance:	IK10
Rated power of the luminaire [W]:	10	Ingress protection:	IP54
Supply voltage [V]:	220-240	Mounting version:	surface
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from 0 to +35
Luminous flux [lm]:	870	Emergency lighting [h]:	2
Luminous efficacy [lm/W]:	87	Net weight [kg]:	0.920
Energy efficiency class:	F	CE certificate:	65/2015
Electrical protection class:	I	Index:	069055/PA
Colour temperature [K]:	4000	EAN:	5905963069055/PA
Colour rendering index:	>80	Category type:	bulkheads
SDCM:	≤ 3	Autotest:	yes
LED lifespan L70B50 [h]:	115000	Warranty [years]:	2 / 0.5 (bateria)
Diffuser material:	PC	ETIM class:	EC002892
Diffuser type:	OPAL	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	PP	Manual:	Download PDF
Colour of the body:	white		

LIGHT CURVES



Card creation date:10 April 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 65/2015



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl