

QUEST 2 LED RESIST M 6600LM DALI I KL. IP66 840 SP10KV (54W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|------------------------------|-----------------|
| Ingress protection: | IP66 |
| Impact resistance: | IK09 |
| Luminous flux [lm]*: | 6600 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | >80 |
| SDCM: | ≤ 3 |
| Electrical protection class: | I |
| Energy efficiency class: | D |
| Material of the body: | aluminium |
| Colour of the body: | anthracite grey |

CHARACTERISTICS

High quality floodlight with integrated LED source. The body is made of die-cast aluminum, powder coated in anthracite gray (RAL 7016) and the mounting bracket is made of black painted steel. The diffuser is tempered glass with a thickness of 5mm. Mounting bracket, corrosion-resistant, with adjustable angle from -140; to +185. Standard equipped with H07RN-F cable and IP66 quick-connector.

APPLICATION

Dedicated for use in swimming pools. Lighting of educational and administrative facilities, halls, garages, passageways, warehouses, stores, food industry and food commodity-related commercial and service facilities.


QUEST 2 LED RESIST M 6600LM DALI I KL. IP66 840 SP10KV (54W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|-----------------|--|------------------------------|
| Index: | 695155 | Ingress protection: | IP66 |
| Light source: | LED module | Mounting version: | surface |
| Rated power of the luminaire [W]: | 54 | Working temperature [°C]: | from -20 to +35 |
| Supply voltage [V]: | 220 - 240 | Lateral surface (SCx) [m2]: | 0.140 |
| Frequency [Hz]: | 50 - 60 | DIMM DALI: | yes |
| Luminous flux [lm]: | 6600 | Cable length [m]: | 0.90 |
| Luminous efficacy [lm/W]: | 122 | Number on the palette [pcs]: | 84 |
| Energy efficiency class: | D | Net weight [kg]: | 4.200 |
| Electrical protection class: | I | Category type: | floodlights |
| Colour temperature [K]: | 4000 | Version: | M |
| Colour rendering index: | >80 | LED lifespan L70B50 [h]: | 125000 |
| SDCM: | ≤ 3 | LED lifespan L80B20 [h]: | 79000 |
| Light colour: | biały | LED lifespan L90B10 [h]: | 38000 |
| Surge protection [kV]: | 10 | Light distribution type: | symmetric 120° |
| Diffuser material: | glass | Warranty [years]: | 5 |
| Diffuser type: | transparent | CE certificate: | 296/2023 |
| Material of the body: | aluminium | Environmental Product Declaration (EPD): | 816/2025 |
| Colour of the body: | anthracite grey | Manual: | Download PDF |
| Dimensions (H/W/T/S) [mm]: | 321/424/37 | Plik LDT: | Download |
| Impact resistance: | IK09 | | |

LIGHT CURVES



QUEST 2 LED RESIST M 6600LM DALI I KL. IP66 840 SP10KV (54W)

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|--|
| 559938 | QUEST PLUS LED M/L wall holder RAL9006 |
| 699993 | QUEST 2 LED M - recessed frame |
| 699986 | QUEST 2 LED L - recessed frame |
| 699962 | QUEST 2 LED L protective grid RAL7016 |
| 699979 | QUEST 2 LED M protective grid RAL7016 |
| 965913 | QUEST 2 LED M/L MAX wall mount RAL7016 |
| 567728 | QUEST 2 LED M/L Pole holder |



QUEST PLUS LED M/L wall holder
RAL9006 (559938)



QUEST 2 LED M - recessed
frame (699993)



QUEST 2 LED L - recessed
frame (699986)



QUEST 2 LED L protective grid
RAL7016 (699962)



QUEST 2 LED M protective grid
RAL7016 (699979)



QUEST 2 LED M/L MAX wall mount
RAL7016 (965913)



QUEST 2 LED M/L Pole
holder (567728)