## QUEST 2 LED RESIST L 19950LM DALI I KL. IP66 840 SP10KV (145W)

**DETAILED CARD** 





## **TECHNICAL PARAMETERS**

Ingress protection: IP66

Impact resistance: IK09

Luminous flux [lm]\*: 19950

Colour temperature [K]: 4000

Color rendering index (Ra) >: 80

**SDCM:** 3

Electrical protection class:

Energy efficiency class: C

Material of the body: aluminium

**Colour of the body:** anthracite grey

### **CHARACTERISTICS**

High quality floodlight with integrated LED source. The body is made of die-cast aluminum, powder coated in anthracite gray (RAL 7016) and the mounting bracket is made of black painted steel. The diffuser is tempered glass with a thickness of 5mm. Mounting bracket, corrosion-resistant, with adjustable angle from -140; to +185. Standard equipped with HO7RN-F cable and IP66 quick-connector.

### APPLICATION

Dedicated for use in swimming pools. Lighting of educational and administrative facilities, halls, garages, passageways, warehouses, stores, food industry and food commodity-related commercial and service facilities.



# **QUEST 2 LED RESIST L 19950LM DALI I KL. IP66 840 SP10KV** (145W)


**DETAILED CARD** 

### **TECHNICAL PARAMETERS TABLE**

Index:	695254
Light source:	LED module
Rated power of the luminaire [W]:	145
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	19950
Luminous efficacy [lm/W]:	138
Energy efficiency class:	С
Electrical protection class:	1
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Light colour:	biały
Surge protection [kV]:	10
Diffuser material:	glass
Diffuser type:	transparent
Material of the body:	aluminium
Colour of the body:	anthracite grey
Dimensions (H/W/T/S) [mm]:	415/424/37
Impact resistance:	IK09

Ingress protection:	IP66	
Mounting version:	surface	
Working temperature [°C]:	from -20 to +35	
Lateral surface (SCx) [m2]: 0.140		
DIMM DALI:	yes	
Cable length [m]:	0.90	
Number on the palette [pcs]:	60	
Net weight [kg]:	4.200	
Category type:	floodlights	
Version:	L	
LED lifespan L70B50 [h]:	125000	
LED lifespan L80B20 [h]:	79000	
LED lifespan L90B10 [h]:	38000	
Light distribution type:	symmetric 120°	
Warranty [years]:	5	
CE certificate:	296/2023	
Environmental Product Declaration (EPD):	<u>816/2025</u>	
Manual:	Download PDF	
Plik LDT:	Download	

## **LIGHT CURVES**






# QUEST 2 LED RESIST L 19950LM DALI I KL. IP66 840 SP10KV (145W)

**DETAILED CARD** 

### **ACCESSORIES AVAILABLE**

index	Name
559938	QUEST PLUS LED M/L wall holder RAL9006
699993	QUEST 2 LED M - recessed frame
699986	QUEST 2 LED L - recessed frame
699962	QUEST 2 LED L protective grid RAL7016
699979	QUEST 2 LED M protective grid RAL7016
965913	QUEST 2 LED M/L MAX wall mount RAL7016
567728	QUEST 2 LED M/L Pole holder




QUEST PLUS LED M/L wall holder RAL9006 (559938)




QUEST 2 LED M - recessed frame (699993)




QUEST 2 LED L - recessed frame (699986)




QUEST 2 LED L protective grid RAL7016 (699962)



QUEST 2 LED M protective grid RAL7016 (699979)



QUEST 2 LED M/L MAX wall mount RAL7016 (965913)



QUEST 2 LED M/L Pole holder (567728)

Card creation date: 10 July 2025



