

MESSAGGIO 701 MM 1100 LM 827 IP20 I CL. 18 W BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Index:	578014
Light source:	LED module
Rated power [W] - range:	18
Luminous flux of the luminaire [lm] - range:	1100
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Electrical protection class:	I
Colour temperature [K]:	2700
Ingress protection:	IP20
Diffuser material:	PC

CHARACTERISTICS

The MESSAGGIO collection, designed by Dorota Koziara, includes pendant lamps with a minimalist form. They can come in all RAL colors, including a multicolor version, where the outside of the housing and the inside of the lamp have different colors. In this way, MESSAGGIO provides unlimited design possibilities.

Thanks to the possibility of adjusting the length of the pendants from the MESSAGGIO lamps, surprising light compositions can be created. Versions with DALI control allow you to change the value of the light output, which further enhances the decorative effect. The milky lampshade is made of PC, while the housing is made of solid yet visually delicate steel, which ensures the durability of the product.

APPLICATION

MESSAGGIO is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO 701 MM 1100 LM 827 IP20 I CL. 18 W BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	578014	Diffuser type:	OPAL
Rated power [W] - range:	18	Colour of the body:	black
EAN:	5905963578014	Diffuser colour:	milky
Luminous flux of the luminaire [lm] - range:	1100	Material of the body:	Steel
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	1230/701/80
Supply voltage [V]:	220 - 240	Mounting dimensions [mm]:	340
Frequency [Hz]:	50 - 60	Ingress protection:	IP20
Colour temperature [K]:	2700	Mounting version:	suspended
Luminous efficacy [lm/W]:	61	Working temperature [°C]:	from -25 to +35
Electrical protection class:	I	Diode PCB material:	aluminium
SDCM:	≤ 3	Net weight [kg]:	2.370
LED lifespan L70B50 [h]:	99000	Warranty [years]:	5
LED lifespan L80B20 [h]:	63000	Category type:	architectural
LED lifespan L90B10 [h]:	31000	CE certificate:	207/2023
Beam angle [°]:	116 x 58	Manual:	Download PDF
Light distribution type:	open space	Plik LDT:	Download
Diffuser material:	PC		

Card creation date:12 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 207/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl