
MESSAGGIO 1261 MM 5400 LM 827 IP20 I CL. DALI 57 W WHITE

DETAILED CARD





TECHNICAL PARAMETERS

Index: 578038

Light source: LED module

Rated power [W] - range: 57

Luminous flux of the luminaire [lm] - $$_{5400}$$

range:

Supply voltage [V]: 220 - 240

Frequency [Hz]: 50 - 60

Electrical protection class:

Colour temperature [K]: 2700

Ingress protection: IP20

Diffuser material: PC

CHARACTERISTICS

The Messaggio collection, designed by Dorota Koziara, includes pendant lamps with a minimalist form. They can come in all RAL colors, including a multicolor version, where the outside of the housing and the inside of the lamp have different colors. In this way, Messaggio provides unlimited design possibilities.

Thanks to the possibility of adjusting the length of the pendants from the Messaggio lamps, surprising light compositions can be created. Versions with DALI control allow you to change the value of the light output, which further enhances the decorative effect. The milky lampshade is made of PC, while the housing is made of solid yet visually delicate steel, which ensures the durability of the product.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.



MESSAGGIO 1261 MM 5400 LM 827 IP20 I CL. DALI 57 W WHITE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	578038
EAN:	5905963578038
Light source:	LED module
Rated power [W] - range:	57
Luminous flux of the luminaire [lm] - range:	5400
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	95
Electrical protection class:	1
Colour temperature [K]:	2700
SDCM:	3
LED lifespan L70B50 [h]:	99000
LED lifespan L80B20 [h]:	63000
LED lifespan L90B10 [h]:	31000
Beam angle [°]:	116 x 58
Light distribution type:	open space
Diffuser material:	PC
Diffuser type:	OPAL

Diffuser colour:	milky
Material of the body:	Steel
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	1230/1261/80
Mounting dimensions [mm]:	340
Ingress protection:	IP20
Mounting version:	suspended
Working temperature [°C]:	from -25 to +35
Diode PCB material:	aluminium
DIMM DALI:	yes
Control:	yes
Net weight [kg]:	4
Warranty [years]:	5
Category type:	decorative fixtures
CE certificate:	207/2023
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 14 November 2025



