MESSAGGIO 701 MM 1100 LM 830 IP20 I CL. 18 W BLACK

DETAILED CARD





TECHNICAL PARAMETERS

Index: 575556

Light source: LED module

Rated power [W] - range: 18

Luminous flux of the luminaire [lm] - 1100

range:

Supply voltage [V]: 220 - 240

Frequency [Hz]: 50 - 60

Electrical protection class:

Colour temperature [K]: 3000

Ingress protection: IP20

Diffuser material: PC

CHARACTERISTICS

The Messaggio collection, designed by Dorota Koziara, includes pendant lamps with a minimalist form. They can come in all RAL colors, including a multicolor version, where the outside of the housing and the inside of the lamp have different colors. In this way, Messaggio provides unlimited design possibilities.

Thanks to the possibility of adjusting the length of the pendants from the Messaggio lamps, surprising light compositions can be created. Versions with DALI control allow you to change the value of the light output, which further enhances the decorative effect. The milky lampshade is made of PC, while the housing is made of solid yet visually delicate steel, which ensures the durability of the product.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.



MESSAGGIO 701 MM 1100 LM 830 IP20 I CL. 18 W BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

ex:	
	575556
N:	5905963575556
nt source:	LED module
ed power [W] - range:	18
ninous flux of the luminaire [lm] - range:	1100
pply voltage [V]:	220 - 240
quency [Hz]:	50 - 60
ninous efficacy [lm/W]:	61
ctrical protection class:	I
our temperature [K]:	3000
CM:	3
lifespan L70B50 [h]:	99000
lifespan L80B20 [h]:	63000
lifespan L90B10 [h]:	31000
ım angle [°]:	116 x 58
nt distribution type:	open space
user material:	PC

Diffuser type:	OPAL
Diffuser colour:	milky
Material of the body:	Steel
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	1230/701/80
Mounting dimensions [mm]:	340
Ingress protection:	IP20
Mounting version:	suspended
Working temperature [°C]:	from -25 to +35
Diode PCB material:	aluminium
Net weight [kg]:	2.370
Warranty [years]:	5
Category type:	decorative fixtures
CE certificate:	207/2023
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 14 November 2025



