


# MESSAGGIO 1261 MM 5400 LM 830 IP20 I CL. DALI 57 W WHITE

## DETAILED CARD



## TECHNICAL PARAMETERS

Index:	575570
Light source:	LED module
Rated power [W] - range:	57
Luminous flux of the luminaire [lm] - range:	5400
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Electrical protection class:	I
Colour temperature [K]:	3000
Ingress protection:	IP20
Diffuser material:	PC

## CHARACTERISTICS

The Messaggio collection, designed by Dorota Koziara, includes pendant lamps with a minimalist form. They can come in all RAL colors, including a multicolor version, where the outside of the housing and the inside of the lamp have different colors. In this way, Messaggio provides unlimited design possibilities.

Thanks to the possibility of adjusting the length of the pendants from the Messaggio lamps, surprising light compositions can be created. Versions with DALI control allow you to change the value of the light output, which further enhances the decorative effect. The milky lampshade is made of PC, while the housing is made of solid yet visually delicate steel, which ensures the durability of the product.

## APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

# MESSAGGIO 1261 MM 5400 LM 830 IP20 I CL. DALI 57 W WHITE

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	575570	Colour of the body:	white
Rated power [W] - range:	57	Diffuser colour:	milky
EAN:	5905963575570	Material of the body:	Steel
Luminous flux of the luminaire [lm] - range:	5400	Dimensions (H/W/T/S) [mm]:	1230/1261/80
Light source:	LED module	Mounting dimensions [mm]:	340
Supply voltage [V]:	220 - 240	Ingress protection:	IP20
Frequency [Hz]:	50 - 60	Mounting version:	suspended
Colour temperature [K]:	3000	Working temperature [°C]:	from -25 to +35
Luminous efficacy [lm/W]:	95	DIMM DALI:	yes
Electrical protection class:	I	Diode PCB material:	aluminium
SDCM:	≤ 3	Control:	yes
LED lifespan L70B50 [h]:	99000	Net weight [kg]:	4
LED lifespan L80B20 [h]:	63000	Warranty [years]:	5
LED lifespan L90B10 [h]:	31000	Category type:	architectural
Beam angle [°]:	116 x 58	CE certificate:	<a href="#">207/2023</a>
Light distribution type:	open space	Manual:	<a href="#">Download PDF</a>
Diffuser material:	PC	Plik LDT:	<a href="#">Download</a>
Diffuser type:	OPAL		

## LIGHT CURVES

