


MESSAGGIO 1261 MM 3300 LM 840 IP20 I CL. DALI 57 W BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Index:	575099
Light source:	LED module
Rated power [W] - range:	57
Luminous flux of the luminaire [lm] - range:	3300
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Electrical protection class:	I
Colour temperature [K]:	4000
Ingress protection:	IP20
Diffuser material:	PC

CHARACTERISTICS

The Messaggio collection, designed by Dorota Koziara, includes pendant lamps with a minimalist form. They can come in all RAL colors, including a multicolor version, where the outside of the housing and the inside of the lamp have different colors. In this way, Messaggio provides unlimited design possibilities.

Thanks to the possibility of adjusting the length of the pendants from the Messaggio lamps, surprising light compositions can be created. Versions with DALI control allow you to change the value of the light output, which further enhances the decorative effect. The milky lampshade is made of PC, while the housing is made of solid yet visually delicate steel, which ensures the durability of the product.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO 1261 MM 3300 LM 840 IP20 I CL. DALI 57 W BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	575099	Diffuser type:	OPAL
EAN:	5905963575099	Diffuser colour:	milky
Light source:	LED module	Material of the body:	Steel
Rated power [W] - range:	57	Colour of the body:	black
Luminous flux of the luminaire [lm] - range:	3300	Dimensions (H/W/T/S) [mm]:	1230/1261/80
Supply voltage [V]:	220 - 240	Mounting dimensions [mm]:	340
Frequency [Hz]:	50 - 60	Ingress protection:	IP20
Luminous efficacy [lm/W]:	58	Mounting version:	suspended
Electrical protection class:	I	Working temperature [°C]:	from -25 to +35
Colour temperature [K]:	4000	Diode PCB material:	aluminium
SDCM:	≤ 3	DIMM DALI:	yes
LED lifespan L70B50 [h]:	99000	Control:	yes
LED lifespan L80B20 [h]:	63000	Net weight [kg]:	4
LED lifespan L90B10 [h]:	31000	Warranty [years]:	5
Beam angle [°]:	116 x 58	Category type:	architectural
Light distribution type:	open space	CE certificate:	207/2023
Diffuser material:	PC	Manual:	Download PDF