

MESSAGGIO BRACKET 1261 MM 3300 - 5400 LM 827 IP20 I CL. 33 - 57 W WHITE

DETAILED CARD



TECHNICAL PARAMETERS

Rated power [W] - range:	33 - 57
Luminous flux of the luminaire [lm] - range:	3300 - 5400
Luminous efficacy [lm/W]:	95
Electrical protection class:	I
Colour temperature [K]:	2700
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Wall lamps from the Messaggio collection, available in a variety of colors and sizes, can create spectacular light and decorative compositions, designed according to the architect's individual concepts. The LED modules used in the lamps ensure a high level of energy efficiency. The steel, solid, yet visually delicate housing can be painted in the interior and exterior parts in two different RAL colors. The milky lampshade is made of impact-resistant polycarbonate.

Messaggio wall lamps also come in a version with DALI control, which allows you to adjust the value of the luminous flux.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO BRACKET 1261 MM 3300 - 5400 LM 827 IP20 I CL. 33 - 57 W WHITE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	578120	Diffuser material:	PC
EAN:	5905963578120	Diffuser type:	OPAL
Rated power [W] - range:	33 - 57	Material of the body:	Steel
Luminous flux of the luminaire [lm] - range:	3300 - 5400	Colour of the body:	white
Supply voltage [V]:	220 - 240	Dimensions (H/W/T/S) [mm]:	128/1261/106
Frequency [Hz]:	50-60	Mounting dimensions [mm]:	340
Luminous efficacy [lm/W]:	95	Ingress protection:	IP20
Electrical protection class:	I	Working temperature [°C]:	from -25 to +35
Colour temperature [K]:	2700	Diode PCB material:	aluminium
SDCM:	≤ 3	Net weight [kg]:	3.640
LED lifespan L70B50 [h]:	99000	Warranty [years]:	5
LED lifespan L80B20 [h]:	63000	Category type:	architectural
LED lifespan L90B10 [h]:	31000	Category of application:	architectural
Beam angle [°]:	116 x 58	CE certificate:	208/2023
Light distribution type:	open space	Manual:	Download PDF
Efficiency of the luminaire:	0.67		

Card creation date: 18 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 208/2023