MESSAGGIO BRACKET 1261 MM 2000 - 3300 LM 827 IP20 I CL. 33 - 57 W BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Rated power [W] - range:	33 - 57
Luminous flux of the luminaire [lm] - range:	2000 - 3300
Luminous efficacy [lm/W]:	58
Electrical protection class:	I
Colour temperature [K]:	2700
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Wall lamps from the Messaggio collection, available in a variety of colors and sizes, can create spectacular light and decorative compositions, designed according to the architect's individual concepts. The LED modules used in the lamps ensure a high level of energy efficiency. The steel, solid, yet visually delicate housing can be painted in the interior and exterior parts in two different RAL colors. The milky lampshade is made of impact-resistant polycarbonate.

Messaggio wall lamps also come in a version with DALI control, which allows you to adjust the value of the luminous flux.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO BRACKET 1261 MM 2000 - 3300 LM 827 IP20 I CL. 33 - 57 W BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	578144	**Diffuser material:**	PC
EAN:	5905963578144	**Diffuser type:**	OPAL
Rated power [W] - range:	33 - 57	**Material of the body:**	Steel
Luminous flux of the luminaire [lm] - range:	2000 - 3300	**Colour of the body:**	black
Supply voltage [V]:	220 - 240	**Dimensions (H/W/T/S) [mm]:**	128/1261/106
Frequency [Hz]:	50-60	**Mounting dimensions [mm]:**	340
Luminous efficacy [lm/W]:	58	**Ingress protection:**	IP20
Electrical protection class:	I	**Working temperature [°C]:**	from -25 to +35
Colour temperature [K]:	2700	**Diode PCB material:**	aluminium
SDCM:	3	**Net weight [kg]:**	4.900
LED lifespan L70B50 [h]:	99000	**Warranty [years]:**	5
LED lifespan L80B10 [h]:	63000	**Category type:**	decorative fixtures
LED lifespan L90B10 [h]:	31000	**Category of application:**	architectural
Beam angle [°]:	116 x 58	**CE certificate:**	208/2023
Light distribution type:	open space	**Manual:**	Download PDF
Efficiency of the luminaire:	0.41	**Plik LDT:**	Download

Card creation date: 12 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 208/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl