

MESSAGGIO BRACKET 1541 MM 2000 - 3400 LM 830 IP20 I CL. 35 - 64 W BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Rated power [W] - range:	35 - 64
Luminous flux of the luminaire [lm] - range:	2000 - 3400
Luminous efficacy [lm/W]:	53
Electrical protection class:	I
Colour temperature [K]:	3000
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Wall lamps from the Messaggio collection, available in a variety of colors and sizes, can create spectacular light and decorative compositions, designed according to the architect's individual concepts. The LED modules used in the lamps ensure a high level of energy efficiency. The steel, solid, yet visually delicate housing can be painted in the interior and exterior parts in two different RAL colors. The milky lampshade is made of impact-resistant polycarbonate.

Messaggio wall lamps also come in a version with DALI control, which allows you to adjust the value of the luminous flux.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO BRACKET 1541 MM 2000 - 3400 LM 830 IP20 I CL. 35 - 64 W BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	575723	Diffuser material:	PC
EAN:	5905963575723	Diffuser type:	OPAL
Rated power [W] - range:	35 - 64	Material of the body:	Steel
Luminous flux of the luminaire [lm] - range:	2000 - 3400	Colour of the body:	black
Supply voltage [V]:	220 - 240	Dimensions (H/W/T/S) [mm]:	128/1541/70
Frequency [Hz]:	50-60	Mounting dimensions [mm]:	340
Luminous efficacy [lm/W]:	53	Ingress protection:	IP20
Electrical protection class:	I	Working temperature [°C]:	from -25 to +35
Colour temperature [K]:	3000	Diode PCB material:	aluminium
SDCM:	≤ 3	Net weight [kg]:	4.440
LED lifespan L70B50 [h]:	99000	Warranty [years]:	5
LED lifespan L80B20 [h]:	63000	Category type:	architectural
LED lifespan L90B10 [h]:	31000	Category of application:	architectural
Beam angle [°]:	116 x 58	CE certificate:	208/2023
Light distribution type:	open space	Manual:	Download PDF
Efficiency of the luminaire:	0.37		

Card creation date: 18 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 208/2023