

MESSAGGIO BRACKET XS 59 LM 827 IP20 I CL. 2 W BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	2
Luminous flux [lm]*:	59
Electrical protection class:	I
Diffuser material:	PC
Diffuser type:	OPAL
Material of the body:	Steel
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	200/130/140

CHARACTERISTICS

Messaggio small wall sconces surprise with their minimalist form and color personalization option. The lamps can be painted in any shade from the RAL palette and create phenomenal light decorations, designed according to the architect's individual concepts. The lamp housing is made of sturdy but visually delicate steel, while the lampshade is made of milky PC.

Messaggio wall lamps also come in a version with DALI control, which allows you to adjust the value of the light output.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO BRACKET XS 59 LM 827 IP20 I CL. 2 W BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	578267	Diffuser material:	PC
EAN:	5905963578267	Diffuser type:	OPAL
Light source:	LED module	Diffuser colour:	milky
Rated power of the luminaire [W]:	2	Material of the body:	Steel
Luminous flux [lm]:	59	Colour of the body:	black
Supply voltage [V]:	220 – 240	Dimensions (H/W/T/S) [mm]:	200/130/140
Frequency [Hz]:	50-60	Ingress protection:	IP20
Electrical protection class:	I	Working temperature [°C]:	from -25 to +35
Colour temperature [K]:	2700	Warranty [years]:	5
SDCM:	≤ 3	Category type:	architectural
LED lifespan L70B50 [h]:	80000	Category of application:	architectural
LED lifespan L80B20 [h]:	55 000	CE certificate:	209/2023
LED lifespan L90B10 [h]:	29000	Manual:	Download PDF
		Plik LDT:	Pobierz

Card creation date: 11 April 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 209/2023