MESSAGGIO BRACKET XS 59 LM 827 IP20 I CL. 2 W BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	2
Luminous flux [lm]*:	59
Electrical protection class:	I
Diffuser material:	PC
Diffuser type:	OPAL
Material of the body:	Steel
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	200/130/140

CHARACTERISTICS

Messaggio small wall sconces surprise with their minimalist form and color personalization option. The lamps can be painted in any shade from the RAL palette and create phenomenal light decorations, designed according to the architect's individual concepts. The lamp housing is made of sturdy but visually delicate steel, while the lampshade is made of milky PC.

Messaggio wall lamps also come in a version with DALI control, which allows you to adjust the value of the light output.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO BRACKET XS 59 LM 827 IP20 I CL. 2 W BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	578267
EAN:	5905963578267
Light source:	LED module
Rated power of the luminaire [W]:	2
Luminous flux [lm]:	59
Supply voltage [V]:	220 – 240
Frequency [Hz]:	50-60
Electrical protection class:	I
Colour temperature [K]:	2700
SDCM:	3
LED lifespan L70B50 [h]:	108000
LED lifespan L80B10 [h]:	108000
LED lifespan L90B10 [h]:	108000
Diffuser material:	PC

Diffuser type:	OPAL
Diffuser colour:	milky
Material of the body:	Steel
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	200/130/140
Ingress protection:	IP20
Working temperature [°C]:	from -25 to +35
Warranty [years]:	5
Category type:	decorative fixtures
Category of application:	architectural
CE certificate:	209/2023
Manual:	Download PDF
ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Plik LDT:	Download

Card creation date: 22 June 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 209/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl