

MESSAGGIO BRACKET XS 59 LM 827 IP20 I CL. DALI 2 W BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	2
Luminous flux [lm]*:	59
Electrical protection class:	I
Diffuser material:	PC
Diffuser type:	OPAL
Material of the body:	Steel
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	200/130/140

CHARACTERISTICS

Messaggio small wall sconces surprise with their minimalist form and color personalization option. The lamps can be painted in any shade from the RAL palette and create phenomenal light decorations, designed according to the architect's individual concepts. The lamp housing is made of sturdy but visually delicate steel, while the lampshade is made of milky PC.

Messaggio wall lamps also come in a version with DALI control, which allows you to adjust the value of the light output.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO BRACKET XS 59 LM 827 IP20 I CL. DALI 2 W BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	578274	Diffuser colour:	milky
EAN:	5905963578274	Material of the body:	Steel
Light source:	LED module	Colour of the body:	black
Rated power of the luminaire [W]:	2	Dimensions (H/W/T/S) [mm]:	200/130/140
Luminous flux [lm]:	59	Ingress protection:	IP20
Supply voltage [V]:	220 – 240	Working temperature [°C]:	from -25 to +35
Frequency [Hz]:	50-60	DIMM DALI:	yes
Electrical protection class:	I	Warranty [years]:	5
Colour temperature [K]:	2700	Category type:	decorative fixtures
SDCM:	3	Category of application:	architectural
LED lifespan L70B50 [h]:	99000	CE certificate:	209/2023
LED lifespan L80B10 [h]:	63000	Manual:	Download PDF
LED lifespan L90B10 [h]:	31000	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Diffuser material:	PC	Plik LDT:	Download
Diffuser type:	OPAL		

Card creation date: 22 June 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 209/2023