MESSAGGIO BRACKET XS 100 LM 840 IP20 I CL. 2 W WHITE

DETAILED CARD





TECHNICAL PARAMETERS

Rated power of the luminaire [W]*: 2

Luminous flux [lm]*: 100

Electrical protection class:

Diffuser material: PC

Diffuser type: OPAL

Material of the body: Steel

Colour of the body: white

Dimensions (H/W/T/S) [mm]: 200/130/140

CHARACTERISTICS

Messaggio small wall sconces surprise with their minimalist form and color personalization option. The lamps can be painted in any shade from the RAL palette and create phenomenal light decorations, designed according to the architect's individual concepts. The lamp housing is made of sturdy but visually delicate steel, while the lampshade is made of milky PC.

Messaggio wall lamps also come in a version with DALI control, which allows you to adjust the value of the light output.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.



MESSAGGIO BRACKET XS 100 LM 840 IP20 I CL. 2 W WHITE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	575488
EAN:	5905963575488
Light source:	LED module
Rated power of the luminaire [W]:	2
Luminous flux [lm]:	100
Supply voltage [V]:	220 – 240
Frequency [Hz]:	50-60
Electrical protection class:	1
Colour temperature [K]:	4000
SDCM:	≤3
LED lifespan L70B50 [h]:	80000
LED lifespan L80B20 [h]:	55 000
LED lifespan L90B10 [h]:	29000
Diffuser material:	PC

Diffuser type:	OPAL
Diffuser colour:	milky
Material of the body:	Steel
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	200/130/140
Ingress protection:	IP20
Working temperature [°C]:	from -25 to +35
Warranty [years]:	5
Category type:	architectural
Category of application:	architectural
CE certificate:	209/2023
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 12 May 2025



