MESSAGGIO STANDING 1241 MM 1400 LM 827 IP20 I CL. DALI SWITCH 23 W BLACK

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Rated power of the luminaire [W]*:	23
Luminous flux [lm]*:	1400
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	61
Electrical protection class:	I
Colour temperature [K]:	2700
LED lifespan L70B50 [h]:	99000
LED lifespan L80B10 [h]:	63000
LED lifespan L90B10 [h]:	31000

CHARACTERISTICS

The Messaggio collection, designed by Dorota Koziara, includes standing lamps - the first of their kind in the brand's portfolio. Their minimalist form and the option of color personalization provide a wide range of arrangement possibilities. Lamps based on LED module technology, provide a high level of energy efficiency. The steel, solid yet visually delicate housing can be painted in the inner and outer parts in two different RAL colors. The milky lampshade is made of impact-resistant polycarbonate.

Messaggio standing lamps are available with DALI control, which allows to adjust the value of the luminous flux.

APPLICATION

Messaggio is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions that will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO STANDING 1241 MM 1400 LM 827 IP20 I CL. DALI SWITCH 23 W BLACK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	578212	**Diffuser colour:**	milky
EAN:	5905963578212	**Material of the body:**	Steel
Light source:	LED module	**Colour of the body:**	black
Rated power of the luminaire [W]:	23	**Dimensions (H/W/T/S) [mm]:**	280/1241
Luminous flux [lm]:	1400	**Ingress protection:**	IP20
Supply voltage [V]:	220 - 240	**Mounting version:**	standing
Frequency [Hz]:	50-60	**Working temperature [°C]:**	from -25 to +35
Luminous efficacy [lm/W]:	61	**Diode PCB material:**	aluminium
Electrical protection class:	I	**DIMM DALI:**	yes
Colour temperature [K]:	2700	**Control:**	yes
SDCM:	3	**Cable length [m]:**	3
LED lifespan L70B50 [h]:	99000	**Net weight [kg]:**	6.200
LED lifespan L80B10 [h]:	63000	**Warranty [years]:**	5
LED lifespan L90B10 [h]:	31000	**Category type:**	decorative fixtures
Beam angle [°]:	116 x 58	**Category of application:**	architectural
Light distribution type:	open space	**CE certificate:**	175/2026
Diffuser material:	PC	**Manual:**	Download PDF
Diffuser type:	OPAL		

Card creation date: 12 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 175/2026

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl