


# SATURN LED HV 10W MAT BIAŁY 4000K

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	184093/HV
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	10
Luminous flux [lm]*:	931
Colour temperature [K]:	4000
Colour rendering index:	80
SDCM:	≤ 3
Electrical protection class:	I
Energy efficiency class:	F

## CHARACTERISTICS

Surface mounted, round LED light fixture with a high luminous flux, high ingress protection class IP54 and an integrated energy-saving light source LED GO!. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). Available ring colors; optional equipment: radio motion sensor (RCR) or PIR sensor.

## APPLICATION

Luminaire is suited for surface mounting on ceilings or walls, intended for outdoor (façade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms. The luminaire is intended for indoor traffic zones included in table 5.1 of the EN12464 standard.

# SATURN LED HV 10W MAT BIAŁY 4000K

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Colour of the body:	white
Nominal power [W]:	10	Dimensions (H/W/T/S) [mm]:	ø335/110
Rated power of the luminaire [W]:	10.80	Impact resistance:	IK10
Supply voltage [V]:	220-240	Ingress protection:	IP54
Frequency [Hz]:	50 - 60	Mounting version:	surface
Luminous flux [lm]:	931	Working temperature [°C]:	from -20 to +35
Luminous efficacy [lm/W]:	87	Net weight [kg]:	1.120
Energy efficiency class:	F	CE certificate:	<a href="#">407/2023</a>
Electrical protection class:	I	Index:	184093/HV
Colour temperature [K]:	4000	EAN:	5905963184093/HV
Colour rendering index:	80	Category type:	bulkheads
SDCM:	≤ 3	Warranty [years]:	5
Power factor:	0.53	ETIM class:	EC002892
LED lifespan L70B50 [h]:	115000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	PC	Manual:	<a href="#">Download PDF</a>
Diffuser type:	OPAL	Plik LDT:	<a href="#">Download</a>
Material of the body:	PP		

## LIGHT CURVES

