

# TIARA 2 LED M 13075LM 740 RM7 IP66 II CL. DALI (76W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	988189
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK10
<b>Rated power of the luminaire [W]*:</b>	76
<b>Luminous flux [lm]*:</b>	13075
<b>Colour temperature [K]:</b>	4000
<b>Color rendering index (Ra) &gt;:</b>	70
<b>Electrical protection class:</b>	II
<b>Optics:</b>	RM7

## CHARACTERISTICS

TIARA 2 LED a new generation of LED road luminaires. It uses directional multi-lens arrays made of PMMA, with each lens having the same optics, ensuring that the light characteristics remain constant over time. The luminaire's dual-chamber design maintains the integrity of the optical chamber during installation work and the opening of the electrical chamber. As standard, the luminaire offers tool-free access to the electrical fixtures using two independent clips, which, if desired and needed to protect against vandalism or uncontrolled opening, can optionally be permanently secured with screws or a seal. The upper part of the luminaire, has dedicated hinges and a safety cable to prevent falling. Using standard tools, quick and convenient service is possible, allowing replacement of any component without the need to disassemble the entire fixture and make soldered connections. The body and handle made of die-cast aluminum, powder-coated in gray, is characterized by a very high degree of IP66 and IK10 impact resistance. Standard features: ergonomic light module suspension system; NTC luminaire accidental overheating protection; fully programmable DALI driver; available functions for maintaining constant lumen output during CLO and autonomous 5-stage power reduction; filter to prevent condensation; connection terminals; tool-free access. Additional options: NEMA, ZHAGA connectors; interfacing with control systems, RCR motion sensor; anti-vandal protection with screws/seal; additional SP10kV protection outside the power supply, on/off power supply without power reduction function; knife disconnect switch that disconnects voltage if the electrical compartment is opened; design with cable terminated with quick disconnect; painting in any RAL color. Certifications: CE, RoHS, ENEC, ENEC+, Zhaga D4i.

## APPLICATION

Thanks to the use of dedicated optics, it is possible to illuminate objects such as: highways, expressways, national, provincial, county, municipal, city, neighborhood, area lighting. Optics are also available to illuminate: pedestrian crossings, sidewalks and bicycle paths.

# TIARA 2 LED M 13075LM 740 RM7 IP66 II CL. DALI (76W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	988189	<b>Dimensions (H/W/T/S) [mm]:</b>	597/265/105
<b>EAN:</b>	5905963988189	<b>Mounting dimensions [mm]:</b>	ø40-60/ø76
<b>ETIM class:</b>	EC000062	<b>Impact resistance:</b>	IK10
<b>Category type:</b>	street lighting	<b>Ingress protection:</b>	IP66
<b>Version:</b>	M	<b>Mounting version:</b>	Top, on pole / Side, on boom
<b>Light source:</b>	LED module	<b>Tilt angle adjustment [°]:</b>	from -30 to +120 (peak) and -120 to +30 (side) in 5° degrees increments
<b>Rated power of the luminaire [W]:</b>	76	<b>Lateral surface (SCx) [m2]:</b>	0.028
<b>Supply voltage [V]:</b>	220 - 240	<b>Working temperature [°C]:</b>	from -40 to +50
<b>Frequency [Hz]:</b>	50 - 60	<b>DIMM DALI:</b>	yes
<b>Luminous flux [lm]:</b>	13075	<b>Control:</b>	Yes + 5-stage power reduction
<b>Luminous efficacy [lm/W]:</b>	172	<b>Protection type:</b>	NTC + ESD
<b>Energy efficiency class:</b>	B	<b>Vandalproof:</b>	yes
<b>Electrical protection class:</b>	II	<b>Net weight [kg]:</b>	5.200
<b>Colour temperature [K]:</b>	4000	<b>ULOR:</b>	0%
<b>Color rendering index (Ra) &gt;:</b>	70	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>SDCM:</b>	5	<b>Technical Warranty:</b>	5 with the possibility of extension to 10
<b>Power factor:</b>	0.98	<b>ENEC Certificate:</b>	<a href="#">0449/ENEC/25; 0163/ENEC+/25</a>
<b>Surge protection [kV]:</b>	10	<b>CE certificate:</b>	<a href="#">07/2024</a>
<b>Diffuser material:</b>	tempered glass	<b>Zhaga-D4i:</b>	<a href="#">ZG407120042023</a>
<b>Diffuser type:</b>	transparent	<b>Environmental Product Declaration (EPD):</b>	<a href="#">682/2024</a>
<b>Optics material:</b>	PMMA	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Optics:</b>	RM7	<b>LED lifespan L95B10 [h]:</b>	100000
<b>Exchangeable source:</b>	yes	<b>Category of application:</b>	Street lighting
<b>Material of the body:</b>	powder coated aluminium	<b>ISO Certificates:</b>	9001:2015, 14001:2015, 45001:2018, 50001:2018
<b>Colour of the body:</b>	grey		

## LIGHT CURVES



# TIARA 2 LED M 13075LM 740 RM7 IP66 II CL. DALI (76W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)
UL01350	Handle fi 76mm for Tiara 2 LED M and Tiara 2 LED S
UL00960	Backshield L (left) Tiara 2 LED M
UL00959	Backshield P (right) Tiara 2 LED M
UL00958	Backshield T (back) Tiara 2 LED M RAL9006 (MOQ 80szt.)
804625	TIARA 2 LED Adjustable bracket Dark Sky diameter 64 mm grey
989766	Tiara 2 LED 64mm handle cover



wall holder (galvanized) (314049)



wall holder (grey) (314056)



Backshield L (left) Tiara 2 LED M (UL00960)



Backshield P (right) Tiara 2 LED M (UL00959)



Backshield T (back) Tiara 2 LED M RAL9006 (MOQ 80szt.) (UL00958)



TIARA 2 LED Adjustable bracket Dark Sky diameter 64 mm grey (804625)



Tiara 2 LED 64mm handle cover (989766)

Card creation date: 19 June 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 07/2024