SATURN LED 14W MAT BIAŁY AW 3H 4000K AUTOTEST

DETAILED CARD

TECHNICAL PARAMETERS

Index:	068713/PA
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	14
Luminous flux [lm]*:	1400
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Electrical protection class:	I
Energy efficiency class:	F

CHARACTERISTICS

Surface mounted, round LED light fixture with a high luminous flux, high ingress protection class IP54 and an integrated energy-saving light source LED GO!. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). Available ring colors; optional equipment: radio motion sensor (RCR) or PIR sensor.

APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for outdoor (façade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms.


SATURN LED 14W MAT BIAŁY AW 3H 4000K AUTOTEST

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	**Impact resistance:**	IK10
Nominal power [W]:	14	**Ingress protection:**	IP54
Rated power of the luminaire [W]:	15	**Mounting version:**	surface
Supply voltage [V]:	220-240	**Working temperature [°C]:**	from -20 to +35
Frequency [Hz]:	50 - 60	**Emergency lighting [h]:**	3
Luminous flux [lm]:	1400	**Net weight [kg]:**	1.100
Luminous efficacy [lm/W]:	94	**CE certificate:**	406/2023
Energy efficiency class:	F	**Index:**	068713/PA
Electrical protection class:	I	**EAN:**	5905963068713/PA
Colour temperature [K]:	4000	**Category type:**	bulkheads
Color rendering index (Ra) >:	80	**Version:**	Antywandal
SDCM:	3	**Autotest:**	yes
LED lifespan L70B50 [h]:	115000	**Warranty [years]:**	2 / 0.5 (bateria)
Diffuser material:	PC	**ETIM class:**	EC002892
Diffuser type:	OPAL	**Vandalproof:**	yes
Material of the body:	PP	**Photobiological safety:**	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour of the body:	white	**Manual:**	Download PDF
Dimensions (H/W/T/S) [mm]:	ø335/110		

LIGHT CURVES



Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 406/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl