

# SATURN LED 18W OPAL BIAŁY 4000K WERSJA ANTYWANDAL

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	069970/PA
<b>Ingress protection:</b>	IP54
<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	18
<b>Luminous flux [lm]*:</b>	1750
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Electrical protection class:</b>	I
<b>Energy efficiency class:</b>	E

## CHARACTERISTICS

Surface mounted, round LED light fixture with a high luminous flux, high ingress protection class IP54 and an integrated energy-saving light source LED GO!. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). Available ring colors; optional equipment: radio motion sensor (RCR) or PIR sensor.

## APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for outdoor (façade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms.

# SATURN LED 18W OPAL BIAŁY 4000K WERSJA ANTYWANDAL

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions (H/W/T/S) [mm]:	ø335/110
Nominal power [W]:	18	Impact resistance:	IK10
Rated power of the luminaire [W]:	18.50	Ingress protection:	IP54
Supply voltage [V]:	220-240	Mounting version:	surface
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -20 to +35
Luminous flux [lm]:	1750	Net weight [kg]:	1.150
Luminous efficacy [lm/W]:	95	CE certificate:	<a href="#">406/2023</a>
Energy efficiency class:	E	Index:	069970/PA
Electrical protection class:	I	EAN:	5905963069970/PA
Colour temperature [K]:	4000	Category type:	bulkheads
Colour rendering index:	>80	Version:	Antywandal
SDCM:	≤ 3	Warranty [years]:	5
LED lifespan L70B50 [h]:	115000	ETIM class:	EC002892
Diffuser material:	PC	Vandalproof:	yes
Diffuser type:	OPAL	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	PP	Manual:	<a href="#">Download PDF</a>
Colour of the body:	white		

## LIGHT CURVES



Card creation date: 06 June 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 406/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)