

CORAL LED EVO PLUS 260MM N 740LM IP44 830 (9W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	223655
Ingress protection:	IP44
Nominal power [W]:	9
Luminous flux [lm]*:	740
Colour temperature [K]:	3000
SDCM:	≤ 3
Electrical protection class:	I
Energy efficiency class:	F
Material of the body:	PP
Ring material:	PP

CHARACTERISTICS

Ceiling lights for ceiling or wall mounting. Luminaire design allows surface and concealed installation. The unique design allows replacement of the LED GO! (light source) module without having to replace the entire luminaire. Integrated design for easy installation. Surface-mounted luminaire allows cable termination.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:
- with a radio motion sensor.

APPLICATION

Suspended mounting board allows quick installation. Removable mounting board available on request as a service kit. Surface wiring. Holes for connection with surface installation, through-wiring possible.


CORAL LED EVO PLUS 260MM N 740LM IP44 830 (9W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Mounting dimensions [mm]:	60
Nominal power [W]:	9	Impact resistance:	IK10
Rated power of the luminaire [W]:	9.40	Ingress protection:	IP44
Supply voltage [V]:	220-240	Mounting version:	surface
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -20 to +35
Luminous flux [lm]:	740	Net weight [kg]:	0.550
Luminous efficacy [lm/W]:	79	Gross weight [kg]:	0.770
Energy efficiency class:	F	Warranty [years]:	5
Electrical protection class:	I	Index:	223655
Colour temperature [K]:	3000	EAN:	5905963223655
Colour rendering index:	>80	Category type:	bulkheads
SDCM:	≤ 3	Product line:	CORAL LED EVO PLUS
Power factor:	0.84	AC voltage range [V]:	198 - 264
Exchangeable source:	yes	DC voltage range [V]:	60
Diffuser material:	PC	LED lifespan L70B50 [h]:	122000
Diffuser type:	OPAL	LED lifespan L80B20 [h]:	78000
Optics material:	PMMA	LED lifespan L90B10 [h]:	39000
Material of the body:	PP	CE certificate:	74/2018
Colour of the body:	white	ETIM class:	EC002892
Ring material:	PP	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Ring colour:	white	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	ø260/108		


LIGHT CURVES



CORAL LED EVO PLUS 260MM N 740LM IP44 830 (9W)

DETAILED CARD

TECHNICAL DETAILS



CORAL LED natynkowe prowadzenie przewodów

CORAL LED EVO PLUS 260MM N 740LM IP44 830 (9W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
223778	CORAL LED EVO PLUS 830 - SERVICE KIT
223792	CORAL LED EVO PLUS 830 RCR - SERVICE KIT
223785	CORAL LED EVO PLUS 840 - SERVICE KIT
223808	CORAL LED EVO PLUS 840 RCR - SERVICE KIT

Card creation date: 18 January 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 74/2018