

# COMPACT LED EVO Z 32W 830 OPAL II KL

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Light source:</b>	LED module
<b>Ingress protection:</b>	IP20
<b>Impact resistance:</b>	IK07
<b>Nominal power [W]:</b>	32
<b>Luminous flux [lm]*:</b>	3550
<b>Colour temperature [K]:</b>	3000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	E
<b>Electrical protection class:</b>	II

## CHARACTERISTICS

Compact LED luminaire designed for suspended installation. Equipped with energy-saving LED panels and an evenly highlighted opal or prismatic diffuser, providing low glare (UGR<19)\*. Made of plastic. Assembly or electrical connection does not require removing the diffuser. Suspension in the set, length 1.2m.

\* The UGR coefficient is met for the typical use of the luminaire

## APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions.

# COMPACT LED EVO Z 32W 830 OPAL II KL

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Nominal power [W]:</b>	32	<b>Impact resistance:</b>	IK07
<b>Index:</b>	628863	<b>Ingress protection:</b>	IP20
<b>Colour temperature [K]:</b>	3000	<b>Mounting version:</b>	suspended
<b>Light source:</b>	LED module	<b>Working temperature [°C]:</b>	from -20 to +35
<b>Luminous flux [lm]:</b>	3550	<b>Net weight [kg]:</b>	5.800
<b>Diffuser type:</b>	OPAL	<b>CE certificate:</b>	<a href="#">360/2023</a>
<b>Rated power of the luminaire [W]:</b>	33	<b>PZH certificate:</b>	<a href="#">B-BK-60212-0070/20</a> <a href="#">B-BK-60212-0042/20</a>
<b>Supply voltage [V]:</b>	220-240	<b>EAN:</b>	5905963628863
<b>Frequency [Hz]:</b>	50 - 60	<b>Category type:</b>	louvres
<b>Energy efficiency class:</b>	E	<b>LED lifespan L70B50 [h]:</b>	132000
<b>Luminous efficacy [lm/W]:</b>	107	<b>LED lifespan L80B20 [h]:</b>	84000
<b>Electrical protection class:</b>	II	<b>LED lifespan L90B10 [h]:</b>	42000
<b>Colour rendering index:</b>	>80	<b>Power factor:</b>	0.95
<b>SDCM:</b>	≤ 3	<b>Warranty [years]:</b>	5
<b>Beam angle [°]:</b>	120	<b>ETIM class:</b>	EC001743
<b>Diffuser material:</b>	PC	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Material of the body:</b>	ABS	<b>UGR (4H8H):</b>	< 19
<b>Colour of the body:</b>	white	<b>Warranty [years]:</b>	5
<b>Dimensions (H/W/T/S) [mm]:</b>	620/620/69	<b>Manual:</b>	<a href="#">Download PDF</a>
		<b>ENEC Certificate:</b>	
		<b>Plik LDT:</b>	<a href="#">Download</a>

## TECHNICAL DETAILS



COMPACT LED EVO Z - SYSTEM  
ZWIESZANIA

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 360/2023