

# COMPACT LED EVO Z 42W 840 PRM II KL

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Light source:</b>	LED module
<b>Ingress protection:</b>	IP20
<b>Impact resistance:</b>	IK07
<b>Nominal power [W]:</b>	42
<b>Luminous flux [lm]*:</b>	5750
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	D
<b>Electrical protection class:</b>	II

## CHARACTERISTICS

Compact LED luminaire designed for suspended installation. Equipped with energy-saving LED panels and an evenly highlighted opal or prismatic diffuser, providing low glare (UGR<19)\*. Made of plastic. Assembly or electrical connection does not require removing the diffuser. Suspension in the set, length 1.2m.

\* The UGR coefficient is met for the typical use of the luminaire

## APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions.

# COMPACT LED EVO Z 42W 840 PRM II KL

DETAILED CARD


## TECHNICAL PARAMETERS TABLE

<b>Nominal power [W]:</b>	42	<b>Dimensions (H/W/T/S) [mm]:</b>	620/620/69
<b>Index:</b>	628894	<b>Impact resistance:</b>	IK07
<b>Colour temperature [K]:</b>	4000	<b>Ingress protection:</b>	IP20
<b>Light source:</b>	LED module	<b>Mounting version:</b>	suspended
<b>Luminous flux [lm]:</b>	5750	<b>Working temperature [°C]:</b>	from -20 to +35
<b>Diffuser type:</b>	PRM	<b>Net weight [kg]:</b>	5.800
<b>Rated power of the luminaire [W]:</b>	43	<b>CE certificate:</b>	<a href="#">360/2023</a>
<b>Supply voltage [V]:</b>	220-240	<b>PZH certificate:</b>	<a href="#">B-BK-60212-0070/20 B-BK-60212-0042/20</a>
<b>Frequency [Hz]:</b>	50 - 60	<b>EAN:</b>	5905963628894
<b>Energy efficiency class:</b>	D	<b>Category type:</b>	louvres
<b>Luminous efficacy [lm/W]:</b>	133	<b>LED lifespan L70B50 [h]:</b>	125000
<b>Electrical protection class:</b>	II	<b>LED lifespan L80B20 [h]:</b>	82000
<b>Colour rendering index:</b>	>80	<b>LED lifespan L90B10 [h]:</b>	40000
<b>SDCM:</b>	≤ 3	<b>Power factor:</b>	0.95
<b>Beam angle [°]:</b>	120	<b>Warranty [years]:</b>	5
<b>Diffuser material:</b>	PC	<b>ETIM class:</b>	EC001743
<b>Material of the body:</b>	ABS	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Colour of the body:</b>	white	<b>Warranty [years]:</b>	5
		<b>Manual:</b>	<a href="#">Download PDF</a>
		<b>ENEC Certificate:</b>	
		<b>Plik LDT:</b>	<a href="#">Pobierz</a>

## TECHNICAL DETAILS



COMPACT LED EVO Z - SYSTEM  
ZWIESZANIA



COMPACT LED EVO PRM

Card creation date: 17 July 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 360/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)