

COMPACT LED EVO P 52W 830 OPAL II KL

DETAILED CARD



TECHNICAL PARAMETERS

Index:	628535
Ingress protection:	IP44/20
Impact resistance:	IK07
Nominal power [W]:	52
Luminous flux [lm]*:	5050
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	E
Material of the body:	ABS

CHARACTERISTICS

Compact LED luminaire designed for recessed installation in modular and plasterboard ceilings. Equipped with energy-saving LED panels and an evenly highlighted opal or prismatic diffuser, providing low glare (UGR<19)*. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

* The UGR coefficient is met for the typical use of the luminaire

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions. The fitting's design is suitable for mounting in 600x600 or 625x625 modular ceilings.


COMPACT LED EVO P 52W 830 OPAL II KL

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	628535	Colour of the body:	white
EAN:	5905963628535	Dimensions (H/W/T/S) [mm]:	595/595/71
Light source:	LED module	Impact resistance:	IK07
Nominal power [W]:	52	Ingress protection:	IP44/20
Rated power of the luminaire [W]:	53	Mounting version:	recessed
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	Net weight [kg]:	2.200
Luminous flux [lm]:	5050	LED lifespan L70B50 [h]:	115000
Luminous efficacy [lm/W]:	95	LED lifespan L80B10 [h]:	72000
Energy efficiency class:	E	Power factor:	0.95
Electrical protection class:	II	ETIM class:	EC002892
Colour temperature [K]:	3000	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Color rendering index (Ra) >:	80	Warranty [years]:	5
SDCM:	3	CE certificate:	455/2023
Beam angle [°]:	120	Environmental Product Declaration (EPD):	944/2026
Diffuser material:	PC	Manual:	Download PDF
Diffuser type:	OPAL	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Material of the body:	ABS	Pliik LDT:	Download

LIGHT CURVES



COMPACT LED EVO P 52W 830 OPAL II KL

DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
630033	Plasterboard mounting brackets (4 pcs)
904349	Safety suspension (modular ceiling)
999543	Plasterboard recessing kit 630x630 white (steel version)
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"




Plasterboard mounting brackets (4 pcs) (630033)



Safety suspension (modular ceiling) (904349)



Plasterboard recessing kit 630x630 white (steel version) (999543)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

Card creation date: 28 April 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 455/2023