

# COMPACT LED EVO P 60W 830 OPAL DALI I KL

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	629617
<b>Ingress protection:</b>	IP44/20
<b>Impact resistance:</b>	IK07
<b>Nominal power [W]:</b>	60
<b>Luminous flux [lm]*:</b>	6300
<b>Colour temperature [K]:</b>	3000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	E
<b>Material of the body:</b>	ABS

## CHARACTERISTICS

Compact LED luminaire designed for recessed installation in modular and plasterboard ceilings. Equipped with energy-saving LED panels and an evenly highlighted opal or prismatic diffuser, providing low glare (UGR<19)\*. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

\* The UGR coefficient is met for the typical use of the luminaire

## APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions. The fitting's design is suitable for mounting in 600x600 or 625x625 modular ceilings.

# COMPACT LED EVO P 60W 830 OPAL DALI I KL

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	60	Colour of the body:	white
Index:	629617	Impact resistance:	IK07
Colour temperature [K]:	3000	Ingress protection:	IP44/20
Light source:	LED module	Mounting version:	recessed
Luminous flux [lm]:	6300	Working temperature [°C]:	from -20 to +35
Diffuser type:	OPAL	Net weight [kg]:	2.200
Rated power of the luminaire [W]:	65	CE certificate:	<a href="#">455/2023</a>
Supply voltage [V]:	220-240	PZH certificate:	<a href="#">B-BK-60212-0070/20 B-BK-60212-0042/20 B-BK-60212-0620/20</a>
DIMM DALI:	yes	EAN:	5905963629617
Frequency [Hz]:	50 - 60	Category type:	louvres
Electrical protection class:	I	LED lifespan L70B50 [h]:	115000
Luminous efficacy [lm/W]:	96	LED lifespan L80B20 [h]:	72000
Dimensions (H/W/T/S) [mm]:	595/595/71	LED lifespan L90B10 [h]:	35000
Energy efficiency class:	E	Warranty [years]:	5
Colour rendering index:	>80	Power factor:	0.98
SDCM:	≤ 3	ETIM class:	EC002892
Diffuser material:	PC	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	ABS	Warranty [years]:	5
		Manual:	<a href="#">Download PDF</a>
		Plik LDT:	<a href="#">Download</a>

# COMPACT LED EVO P 60W 830 OPAL DALI I KL

DETAILED CARD

## ACCESSORIES AVAILABLE


index	Name
630033	Plasterboard mounting brackets (4 pcs)
904349	Safety suspension (modular ceiling)
999543	Plasterboard recessing kit 630x630 white (steel version)
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"




Plasterboard mounting brackets (4 pcs) (630033)



Safety suspension (modular ceiling) (904349)



Plasterboard recessing kit 630x630 white (steel version) (999543)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

Card creation date: 19 June 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 455/2023