

# COMPACT LED EVO P 4250LM PRM II KL IP54/IP20 595X595 830 (32W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	630835
<b>Ingress protection:</b>	IP54/20
<b>Impact resistance:</b>	IK07
<b>Nominal power [W]:</b>	32
<b>Luminous flux [lm]*:</b>	4250
<b>Colour temperature [K]:</b>	3000
<b>SDCM:</b>	3
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	ABS

## CHARACTERISTICS

Compact LED luminaire designed for recessed installation in modular and plasterboard ceilings. Equipped with energy-saving LED panels and an evenly highlighted opal or prismatic diffuser, providing low glare (UGR<19)\*. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

\* The UGR coefficient is met for the typical use of the luminaire

## APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions. The fitting's design is suitable for mounting in 600x600 or 625x625 modular ceilings.

# COMPACT LED EVO P 4250LM PRM II KL IP54/IP20


## 595X595 830 (32W)

DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	630835	Ingress protection:	IP54/20
Light source:	LED module	Mounting version:	recessed
Nominal power [W]:	32	Working temperature [°C]:	od -20 do +35
Rated power of the luminaire [W]:	33	Net weight [kg]:	2
Frequency [Hz]:	50 - 60	LED lifespan L70B50 [h]:	132000
Luminous flux [lm]:	4250	LED lifespan L80B10 [h]:	84000
Luminous efficacy [lm/W]:	128	Power factor:	0.95
Energy efficiency class:	D	ETIM class:	EC002892
Electrical protection class:	II	UGR (4H8H):	< 19
Colour temperature [K]:	3000	Photobiological safety:	RG0 - exempt (no photobiological hazard)
SDCM:	3	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	<a href="#">358/2023</a>
Diffuser type:	PRM	PZH certificate:	<a href="#">B-BK-60212-0070/20 B-BK-60212-0042/20 B-BK-60212-0620/20</a>
Material of the body:	ABS	Manual:	<a href="#">Download PDF</a>
Colour of the body:	white	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Dimensions (H/W/T/S) [mm]:	595/595/71	Plik LDT:	<a href="#">Download</a>
Impact resistance:	IK07		

### LIGHT CURVES



# COMPACT LED EVO P 4250LM PRM II KL IP54/IP20 595X595 830 (32W)

---

DETAILED CARD  
**TECHNICAL DETAILS**

---



COMPACT LED EVO PRM

# COMPACT LED EVO P 4250LM PRM II KL IP54/IP20

## 595X595 830 (32W)

DETAILED CARD

### ACCESSORIES AVAILABLE


index	Name
630033	Plasterboard mounting brackets (4 pcs)
904349	Safety suspension (modular ceiling)
999543	Plasterboard recessing kit 630x630 white (steel version)
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"



Plasterboard mounting brackets (4 pcs) (630033)



Safety suspension (modular ceiling) (904349)



Plasterboard recessing kit 630x630 white (steel version) (999543)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

Card creation date: 23 March 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 358/2023