

# COMPACT LED EVO P 3800LM PLX II KL IP54/IP20 595X595 840 (32W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	630804
Ingress protection:	IP54/20
Impact resistance:	IK07
Nominal power [W]:	32
Luminous flux [lm]*:	3800
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	D
Material of the body:	ABS

## CHARACTERISTICS

Compact LED luminaire designed for recessed installation in modular and plasterboard ceilings. Equipped with energy-saving LED modules and an evenly highlighted opal or prismatic diffuser, providing low glare (UGR<19)\*. Made of plastic. Assembly or electrical connection does not require removing the diffuser

## APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions. The fitting's design is suitable for mounting in 600x600 or 625x625 modular ceilings.

# COMPACT LED EVO P 3800LM PLX II KL IP54/IP20 595X595 840 (32W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	630804	Ingress protection:	IP54/20
Light source:	LED module	Mounting version:	recessed
Nominal power [W]:	32	Working temperature [°C]:	od -20 do +35
Rated power of the luminaire [W]:	33	Net weight [kg]:	2
Frequency [Hz]:	50 - 60	PZH certificate:	<a href="#">B-BK-60212-0070/20</a> <a href="#">B-BK-60212-0042/20</a> <a href="#">B-BK-60212-0620/20</a>
Luminous flux [lm]:	3800	Category type:	troffers
Luminous efficacy [lm/W]:	115	LED lifespan L70B50 [h]:	132000
Energy efficiency class:	D	LED lifespan L80B20 [h]:	84000
Electrical protection class:	II	LED lifespan L90B10 [h]:	42000
Colour temperature [K]:	4000	Power factor:	0.95
SDCM:	≤ 3	ETIM class:	EC002892
Diffuser material:	PC	UGR (4H8H):	< 19
Diffuser type:	OPAL	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Material of the body:	ABS	Warranty [years]:	5
Colour of the body:	white	CE certificate:	<a href="#">358/2023</a>
Dimensions (H/W/T/S) [mm]:	595/595/71	Manual:	<a href="#">Download PDF</a>
Impact resistance:	IK07		

## LIGHT CURVES



# COMPACT LED EVO P 3800LM PLX II KL IP54/IP20 595X595 840 (32W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
630033	Plasterboard mounting brackets (4 pcs)
904349	Safety suspension (modular ceiling)
999543	Plasterboard recessing kit 630x630 white (steel version)
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"



Plasterboard mounting brackets (4 pcs) (630033)



Safety suspension (modular ceiling) (904349)



Plasterboard recessing kit 630x630 white (steel version) (999543)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

Card creation date: 11 July 2025  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 358/2023