

COMPACT LED EVO P 5350LM PRM II KL IP54/IP20

595X595 830 (42W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	630910
Ingress protection:	IP54/20
Impact resistance:	IK07
Nominal power [W]:	42
Luminous flux [lm]*:	5350
Colour temperature [K]:	3000
SDCM:	3
Energy efficiency class:	D
Material of the body:	ABS

CHARACTERISTICS

Compact LED luminaire designed for recessed installation in modular and plasterboard ceilings. Equipped with energy-saving LED panels and an evenly highlighted opal or prismatic diffuser, providing low glare (UGR<19)*. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

* The UGR coefficient is met for the typical use of the luminaire

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions. The fitting's design is suitable for mounting in 600x600 or 625x625 modular ceilings.

COMPACT LED EVO P 5350LM PRM II KL IP54/IP20


595X595 830 (42W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	630910	Impact resistance:	IK07
Light source:	LED module	Ingress protection:	IP54/20
Nominal power [W]:	42	Mounting version:	recessed
Rated power of the luminaire [W]:	43	Working temperature [°C]:	od -20 do +35
Frequency [Hz]:	50 - 60	Net weight [kg]:	2
Luminous flux [lm]:	5350	LED lifespan L70B50 [h]:	125000
Luminous efficacy [lm/W]:	124	LED lifespan L80B10 [h]:	82000
Energy efficiency class:	D	Power factor:	0.95
Electrical protection class:	II	ETIM class:	EC002892
Colour temperature [K]:	3000	Photobiological safety:	RG0 - exempt (no photobiological hazard)
SDCM:	3	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	358/2023
Diffuser type:	PRM	Environmental Product Declaration (EPD):	944/2026
Material of the body:	ABS	Manual:	Download PDF
Colour of the body:	white	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Dimensions (H/W/T/S) [mm]:	595/595/71	Plik LDT:	Download

LIGHT CURVES



COMPACT LED EVO P 5350LM PRM II KL IP54/IP20 595X595 830 (42W)

DETAILED CARD

TECHNICAL DETAILS



COMPACT LED EVO PRM

COMPACT LED EVO P 5350LM PRM II KL IP54/IP20 595X595 830 (42W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
630033	Plasterboard mounting brackets (4 pcs)
904349	Safety suspension (modular ceiling)
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"
998973	Frame steel white gloss RAL9016 600x600 SM "well effect"



Plasterboard mounting brackets (4 pcs) (630033)




Safety suspension (modular ceiling) (904349)



Frame adapter KG 635x635 WHITE (374845)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)



Frame steel white gloss RAL9016 600x600 SM "well effect" (998973)

Card creation date: 28 April 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 358/2023