
# COMPACT LED EVO P 5050LM PLX II KL IP54/IP20 595X595 830 (52W)

**DETAILED CARD** 





## **TECHNICAL PARAMETERS**

Index:	630996
Ingress protection:	IP54/20
Impact resistance:	IK07
Nominal power [W]:	52
Luminous flux [lm]*:	5050
Colour temperature [K]:	3000
SDCM:	3
Energy efficiency class:	E
Material of the body:	ABS

### **CHARACTERISTICS**

Compact LED luminaire designed for recessed installation in modular and plasterboard ceilings. Equipped with energy-saving LED panels and an evenly highlighted opal or prismatic diffuser, providing low glare (UGR<19)\*. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

## **APPLICATION**

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions. The fitting's design is suitable for mounting in 600x600 or 625x625 modular ceilings.



<sup>\*</sup> The UGR coefficient is met for the typical use of the luminaire

# COMPACT LED EVO P 5050LM PLX II KL IP54/IP20 595X595 830 (52W)


**DETAILED CARD** 

## **TECHNICAL PARAMETERS TABLE**

Index:	630996
Light source:	LED module
Nominal power [W]:	52
Rated power of the luminaire [W]:	53
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	5050
Luminous efficacy [lm/W]:	95
Energy efficiency class:	
Electrical protection class:	1
Colour temperature [K]:	3000
SDCM:	3
Diffuser material:	PC
Diffuser type:	OPAL
Material of the body:	ABS
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	595/595/71
Impact resistance:	IK07

Ingress protection:	IP54/20
Mounting version:	recessed
Working temperature [°C]:	od -20 do +35
Net weight [kg]:	2
PZH certificate:	B-BK-60212-0070/20 B-BK- 60212-0042/20 B-BK-60212- 0620/20
Category type:	troffers
LED lifespan L70B50 [h]:	115000
LED lifespan L80B20 [h]:	72000
LED lifespan L90B10 [h]:	35000
Power factor:	0.95
ETIM class:	EC002892
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Warranty [years]:	5
CE certificate:	<u>358/2023</u>
Manual:	Download PDF
Plik LDT:	Download

## **LIGHT CURVES**



# COMPACT LED EVO P 5050LM PLX II KL IP54/IP20 595X595 830 (52W)

**DETAILED CARD** 

## **ACCESSORIES AVAILABLE**


index	Name
630033	Plasterboard mounting brackets (4 pcs)
904349	Safety suspension (modular ceiling)
999543	Plasterboard recessing kit 630x630 white (steel version)
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"




Plasterboard mounting brackets (4 pcs) (630033)



Safety suspension (modular ceiling) (904349)



Plasterboard recessing kit 630x630 white (steel version) (999543)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

Card creation date: 11 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

