

CORAL LED EVO 260MM P 750LM IP44 840 (9W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	223921
Ingress protection:	IP44
Nominal power [W]:	9
Luminous flux [lm]*:	750
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	F
Material of the body:	PP
Ring material:	PP
Diffuser material:	PC

CHARACTERISTICS

Ceiling lights for ceiling or wall mounting. Luminaire design allows surface and concealed installation. The unique design allows replacement of the LED GO! (light source) module without having to replace the entire luminaire. Integrated design for easy installation. Surface-mounted luminaire allows cable termination.

APPLICATION

Suspended mounting board allows quick installation. Removable mounting board available on request as a service kit. Surface wiring. Holes for connection with surface installation, through-wiring possible.


CORAL LED EVO 260MM P 750LM IP44 840 (9W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions (H/W/T/S) [mm]:	ø260/108
Nominal power [W]:	9	Mounting dimensions [mm]:	ø220
Rated power of the luminaire [W]:	9.90	Impact resistance:	IK10
Supply voltage [V]:	220-240	Ingress protection:	IP44
Frequency [Hz]:	50 - 60	Mounting version:	recessed
Luminous flux [lm]:	750	Working temperature [°C]:	from -20 to +35
Luminous efficacy [lm/W]:	76	Net weight [kg]:	0.660
Energy efficiency class:	F	Gross weight [kg]:	0.880
Electrical protection class:	I	Warranty [years]:	5
Colour temperature [K]:	4000	Index:	223921
Colour rendering index:	>80	EAN:	5905963223921
SDCM:	≤ 3	Category type:	bulkheads
Power factor:	0.61	Product line:	CORAL LED EVO
Exchangeable source:	yes	AC voltage range [V]:	220 - 240
Diffuser material:	PC	LED lifespan L70B50 [h]:	86000
Diffuser type:	OPAL	LED lifespan L80B20 [h]:	54000
Optics material:	PMMA	LED lifespan L90B10 [h]:	26000
Material of the body:	PP	CE certificate:	73/2018
Colour of the body:	white	ETIM class:	EC002892
Ring material:	PP	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Ring colour:	white	Manual:	Download PDF


LIGHT CURVES



CORAL LED EVO 260MM P 750LM IP44 840 (9W)

DETAILED CARD

TECHNICAL DETAILS



CORAL LED natynkowe prowadzenie przewodów

CORAL LED EVO 260MM P 750LM IP44 840 (9W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
223969	CORAL LED EVO 830 - SERVICE KIT
223983	CORAL LED EVO 830 RCR - SERVICE KIT
223976	CORAL LED EVO 840 - SERVICE KIT
223990	CORAL LED EVO 840 RCR - SERVICE KIT

Card creation date: 10 September 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 73/2018