

INDO LED EVO P 3450LM PLX 830 (34W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	380952
Ingress protection:	IP20
Nominal power [W]:	34
Luminous flux [lm]*:	3450
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	powder coated steel
Diffuser material:	PMMA
Diffuser type:	OPAL

CHARACTERISTICS

Recessed mounted square luminaire with an integrated energy-saving LED light source. Powder-coated steel body. The lens diffuser is made of metal sheet and opalized PMMA. It provides comfortable and soft light.

APPLICATION

A versatile indoor luminaire designed for office rooms and areas of general public use. Suitable as a general light source for all sorts of work that require optical focus. Dedicated for new applications and as a replacement of traditional T8 and T5 tube luminaires with energy-saving LED lamps


INDO LED EVO P 3450LM PLX 830 (34W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	380952	Diffuser type:	OPAL
Light source:	LED module	Material of the body:	powder coated steel
Nominal power [W]:	34	Colour of the body:	white
Rated power of the luminaire [W]:	36.80	Dimensions (H/W/T/S) [mm]:	106/595/595
Supply voltage [V]:	220-240	Impact resistance:	IK07
Frequency [Hz]:	50 - 60	Ingress protection:	IP20
Luminous flux [lm]:	3450	Mounting version:	recessed
Luminous efficacy [lm/W]:	93	Working temperature [°C]:	from -20 to +35
Energy efficiency class:	E	EAN:	5905963380952
Electrical protection class:	I	Category type:	louvres
Colour temperature [K]:	3000	AC voltage range [V]:	198 – 264
Colour rendering index:	>80	ETIM class:	EC002892
SDCM:	≤ 3	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Power factor:	0.96	Warranty [years]:	5
LED lifespan L70B50 [h]:	50 000	Manual:	Download PDF
Diffuser material:	PMMA	CE certificate:	367/2023

LIGHT CURVES



INDO LED EVO P 3450LM PLX 830 (34W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)



Plasterboard recessing kit 630x630
white (steel version) (999543)

Card creation date: 25 January 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 367/2023