### TIARA LED L PRO 39025LM 740 RM3 IP66 II CL. DALI (305W)

**DETAILED CARD** 





### **TECHNICAL PARAMETERS**

Index:	924972
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	305
Luminous flux [lm]*:	39025
Colour temperature [K]:	4000
Color rendering index (Ra) >:	70
Electrical protection class:	II
Optics:	RM3

### **CHARACTERISTICS**

TIARA LED PRO a family of LED road luminaires based on a proven form factor. It uses directional multi-lens matrices, made of PMMA, with each lens having the same optics, ensuring that the luminous characteristics remain constant over time. Components from renowned manufacturers and new LED panels contribute to the very high luminous efficacy achieved at the output of the luminaire - reaching 170 lm/W. The two-chamber construction of the luminaire maintains the tightness of the optical chamber during assembly work and allows tool-free access to the electrical equipment chamber. The upper part of the luminaire, has dedicated hinges and a safety cord. Using standard tools, quick and convenient servicing is possible, allowing the replacement of any component without having to dismantle the entire luminaire and make soldered connections. The body and handle are made of diecast aluminium, powder-coated grey, and have a very high IP66 protection rating and IKO9 mechanical impact resistance. Standard features: ergonomic light module suspension system; fully programmable DALI driver; CLO constant lumen maintenance and autonomous 5-stage power reduction functions available; NTC overheating protection; filter to prevent condensation; connection terminals; tool-free access. Additional options: NEMA, ZHAGA connectors; interfacing with control systems, RCR motion sensor; additional SP10kV protection outside the power supply, on/off power supply without power reduction function; knife disconnector to disconnect voltage if the electrical compartment is opened; design with cable terminated with quick disconnect; painting in any RAL colour. Certifications: CE, RoHS, ENEC, ENEC+, Zhaga D4i.

#### **APPLICATION**

Thanks to the use of dedicated optics, it is possible to illuminate objects such as: motorways, motorways, national roads, voivodeships, districts, communes, municipalities, housing estates, area lighting. Optics are also available to illuminate: pedestrian crossings, pavements and cycle paths.



## TIARA LED L PRO 39025LM 740 RM3 IP66 II CL. DALI (305W)


**DETAILED CARD** 

### **TECHNICAL PARAMETERS TABLE**

Index:	924972
EAN:	5905963924972
ETIM class:	EC000062
Category type:	street lighting
Version:	L
Light source:	LED module
Rated power of the luminaire [W]:	305
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	39025
Luminous efficacy [lm/W]:	128
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	70
SDCM:	5
Surge protection [kV]:	10
Diffuser material:	tempered glass
Diffuser type:	transparent
Optics material:	PMMA
Optics:	RM3
Exchangeable source:	yes

Material of the body:	powder coated aluminium
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	870/122/262
Mounting dimensions [mm]:	ø60
Impact resistance:	IK09
Ingress protection:	IP66
Mounting version:	Top, on pole / Side, on boom
Tilt angle adjustment [°]:	-5 to +15 (peak); -15 to +5 (side)
Lateral surface (SCx) [m2]:	0.034
Working temperature [°C]:	from -40 to +35
DIMM DALI:	yes
Control:	V   F -t
Control.	Yes + 5-stage power reduction
Net weight [kg]:	6.500
	3 1
Net weight [kg]:	6.500
Net weight [kg]: ULOR:	6.500  0%  Risk Group 1 (no photobiological hazard under normal behavioral limitation)  5 with the possibility of extension to 10
Net weight [kg]: ULOR: Photobiological safety:	6.500  0%  Risk Group 1 (no photobiological hazard under normal behavioral limitation)  5 with the possibility of
Net weight [kg]: ULOR: Photobiological safety: Technical Warranty:	6.500  0%  Risk Group 1 (no photobiological hazard under normal behavioral limitation)  5 with the possibility of extension to 10  0356/ENEC/24/M1/A1;
Net weight [kg]: ULOR: Photobiological safety: Technical Warranty: ENEC Certificate:	6.500  0%  Risk Group 1 (no photobiological hazard under normal behavioral limitation)  5 with the possibility of extension to 10  0356/ENEC/24/M1/A1; 0120/ENEC+/24/M1/A1
Net weight [kg]: ULOR: Photobiological safety: Technical Warranty: ENEC Certificate: CE certificate:	6.500  0%  Risk Group 1 (no photobiological hazard under normal behavioral limitation)  5 with the possibility of extension to 10  0356/ENEC/24/M1/A1; 0120/ENEC+/24/M1/A1  95/2023

### **LIGHT CURVES**





# TIARA LED L PRO 39025LM 740 RM3 IP66 II CL. DALI (305W)

**DETAILED CARD** 

### **ACCESSORIES AVAILABLE**

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)
UL00184	mounting grip 78 mm TIARA LED







wall holder (galvanized) (314049)

wall holder (grey) (314056)

mounting grip 78 mm TIARA LED (UL00184)

Card creation date: 03 June 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

