

FLATO LED M 1750LM 840 IP54 II KL. 3M WT.UNI-SCHUKO GREY (17W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	622427
Ingress protection:	IP54
Impact resistance:	IK08
Rated power of the luminaire [W]*:	17
Luminous flux [lm]*:	1750
Colour temperature [K]:	4000
Material of the body:	PP
Colour of the body:	graphite
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Compact LED floodlight ensuring even and stable directional lighting. The body, made of copolymer with rubber, increases its durability. The luminaire is equipped with anti-glare diffuser made of frosted PC with an UV stabiliser, which, despite the matt surface, transmits up to 80% of the light emitted by the diodes.

APPLICATION

It can be used in general lighting applications: building façades, outbuildings, courtyards, in front of building entrances, billboards, advertisement boards and as a workplace luminaire for e.g. illuminating workplaces, workshops, construction sites. The smaller size and compact design make it more convenient to transport. The luminaire is designed for outdoor use, industrial applications or other applications where the lighting standards allow CRI <80.

FLATO LED M 1750LM 840 IP54 II KL. 3M WT.UNI-SCHUKO GREY (17W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	622427	Colour of the body:	graphite
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	132/185/74
Rated power of the luminaire [W]:	17	Impact resistance:	IK08
Nominal power [W]:	17	Ingress protection:	IP54
Supply voltage [V]:	220-240	Plug type:	UNI-SCHUKO
Luminous flux [lm]:	1750	Cable length [m]:	3
Colour temperature [K]:	4000	Category type:	floodlights, workplace floodlights
Beam angle [°]:	120	Manual:	Download PDF
Diffuser material:	PC	CE certificate:	186/2023
Diffuser type:	OPAL	Energy efficiency class:	E
Material of the body:	PP	ETIM class:	EC001744

Card creation date: 28 March 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 186/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl