

# PORTAL EMERGENCY 250LM 20M AT IP54 1H+ SET OF 6 PICTOGRAMS

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	736704
Ingress protection:	IP54
Nominal power [W]:	3
Luminous flux [lm]*:	250
Colour temperature [K]:	4000
Colour rendering index:	80
SDCM:	≤ 3
Energy efficiency class:	G
Diffuser material:	PC
Diffuser type:	transparent

## CHARACTERISTICS

Emergency Portal is a luminaire designed to illuminate open spaces and to indicate the direction of evacuation through the use of pictograms. A modern emergency module with an automatic test ensures maintenance-free reporting of errors or the need to replace the battery. Efficient LEDs of the latest generation ensure adequate illumination of escape routes.

## APPLICATION

The high level of protection IP54 allows for use in industrial spaces, and the slender, timeless and neutral body of the luminaire will also be perfect for public facilities - offices, restaurants, commercial facilities. The possibility of ceiling and wall mounting extends the range of possible applications.

# PORTAL EMERGENCY 250LM 20M AT IP54 1H+ SET OF 6 PICTOGRAMS

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	736704	Diffuser type:	transparent
EAN:	5905963736704	Diffuser colour:	transparent
Light source:	LED module	Optics material:	ABS
Nominal power [W]:	3	Optics:	PC
Rated power of the luminaire [W]:	3	Colour of the body:	white
Supply voltage [V]:	3	Dimensions (H/W/T/S) [mm]:	280/185/55
Frequency [Hz]:	50-60	Ingress protection:	IP54
Luminous flux [lm]:	250	Mounting version:	surface
Luminous efficacy [lm/W]:	88	Working temperature [°C]:	from 0 to +35
Energy efficiency class:	G	Net weight [kg]:	0.730
Electrical protection class:	II	Category type:	emergency lighting, dual-function luminaires
Colour temperature [K]:	4000	AC voltage range [V]:	207-253
Colour rendering index:	80	Emergency lighting [h]:	1
SDCM:	≤ 3	Autotest:	yes
Power factor:	0.90	CE certificate:	<a href="#">50/2023</a>
LED lifespan L70B50 [h]:	100000	Manual:	<a href="#">Download PDF</a>
Beam angle [°]:	120	CNBOP certificate:	<a href="#">5147/2023</a>
Diffuser material:	PC		

Card creation date:10 July 2024  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 50/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)