

# PORTAL EMERGENCY 100LM AT IP54 3H

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	736728
Ingress protection:	IP54
Nominal power [W]:	1
Luminous flux [lm]*:	100
Colour temperature [K]:	4000
Colour rendering index:	80
SDCM:	≤ 3
Energy efficiency class:	G
Diffuser material:	PC
Diffuser type:	transparent

## CHARACTERISTICS

Emergency Portal is a luminaire designed to illuminate open spaces and to indicate the direction of evacuation through the use of pictograms. A modern emergency module with an automatic test ensures maintenance-free reporting of errors or the need to replace the battery. Efficient LEDs of the latest generation ensure adequate illumination of escape routes.

## APPLICATION

The high level of protection IP54 allows for use in industrial spaces, and the slender, timeless and neutral body of the luminaire will also be perfect for public facilities - offices, restaurants, commercial facilities. The possibility of ceiling and wall mounting extends the range of possible applications.

# PORTAL EMERGENCY 100LM AT IP54 3H

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	736728	Diffuser type:	transparent
EAN:	5905963736728	Diffuser colour:	transparent
Light source:	LED module	Optics material:	ABS
Nominal power [W]:	1	Optics:	PC
Rated power of the luminaire [W]:	1	Colour of the body:	white
Supply voltage [V]:	3	Dimensions (H/W/T/S) [mm]:	280/185/55
Frequency [Hz]:	50-60	Ingress protection:	IP54
Luminous flux [lm]:	100	Mounting version:	surface
Luminous efficacy [lm/W]:	139	Working temperature [°C]:	from 0 to +35
Energy efficiency class:	G	Net weight [kg]:	0.730
Electrical protection class:	II	Category type:	emergency lighting, dual-function luminaires
Colour temperature [K]:	4000	AC voltage range [V]:	207-253
Colour rendering index:	80	Emergency lighting [h]:	3
SDCM:	≤ 3	Autotest:	yes
Power factor:	0.95	CE certificate:	<a href="#">50/2023</a>
LED lifespan L70B50 [h]:	100000	Manual:	<a href="#">Download PDF</a>
Beam angle [°]:	120	CNBOP certificate:	<a href="#">5147/2023</a>
Diffuser material:	PC		